

# A230 - 2K Plastic Additive




## **Descripción:**

A230 2K es un aditivo cuyas propiedades permiten aplicar un aparejo 2K directamente sobre zonas plásticas sin necesidad de aplicar un adherente para plásticos 1K.

## **Uso:**

- Con aparejos Hyflow
- No usar con: P97 Wash Primer, 1K productos , P908 Epoxy Primer.

## **Aplicación del product:**



1:15  
15% A230 2K Plastic Aditive | 100% 2K Primer.



Spray Nozzle 1.4 – 1.6 mm  
2.0 – 2.2 bar inlet pressure



Light dry sanding with P400 - P500 grit



Clean Surface with Genclean S241 degreaser to remove contamination prior to top coating



Wear suitable protection

## **Product Characteristics**

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.

## A230 - 2K Plastic Additive



|                          |                                                                                                                                                                                                     |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>VOC(2004/42/EC):</b>  | 2004/42/IIB (c) (540)540. The EU limit value for this product (product category IIB.c) in ready to use form is max 540g/ltr. The VOC content of this product in ready for use form is max. 540 g/l. |
| <b>Specific Gravity:</b> | 1.105 kg/cm <sup>3</sup>                                                                                                                                                                            |
| <b>Flash Point:</b>      | 20 (77 °F)                                                                                                                                                                                          |
| <b>Solid Content:</b>    | 42.5 % by weight pre-dilution                                                                                                                                                                       |
| <b>Coverage:</b>         | 10-11 m <sup>2</sup> /l at 25-micron film thickness (theoretical)                                                                                                                                   |
| <b>SDS:</b>              | Refer to the Safety Data Sheet                                                                                                                                                                      |

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.