
Page 1/12

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 07.08.2024



Page 2/12

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 07.08.2024

Trade name: C100 2K PLASTICISER GLOSS

	(Contd. of page 1)
2.2 Label el	ements
Labelling ad	cording to Regulation (EC) No 1272/2008
The product	is classified and labelled according to the GB CLP regulation.
Hazard picto	ograms
^	A
Jul /	
<u><u><u> </u></u></u>	
GHS02 GH	HS07
Signal word	Warning
Hazard state	
	hable liquid and vapour.
	s skin irritation.
	I to aquatic life with long lasting effects.
	ny statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources
	No smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing
	protection.
P303+P361+	P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse ski
	with water [or shower].
P501	Dispose of contents/container in accordance with local/regional/national
	international regulations.
Additional i	
	s(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4
	nyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-, n-butyl acrylate, methyl methacrylate
	acrylate, methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate. May produce an allergi
reaction.	
2.3 Other ha	
	PBT and vPvB assessment
PBT: Not ap	
vPvB: Not a	pplicable.

(Contd. on page 3)

Page 3/12

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 07.08.2024

Trade name: C100 2K PLASTICISER GLOSS

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation:	Mixtures
--------------------------------	----------

· Description: Mixture of substances listed below with nonhazardous additions.

CAS: 1330-20-7	xylene	>25- <i>≤</i> 50%
EINECS: 215-535-7	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
EINECS: 202-849-4	ethylbenzene � Flam. Liq. 2, H225; � STOT RE 2, H373; Asp. Tox. 1, H304; 🕦 Acute Tox. 4, H332	>2.5- <i>≤</i> 10%
L	n-butyl acetate 📀 Flam. Liq. 3, H226; 🕐 STOT SE 3, H336	<i>≤</i> 2.5%
Reg.nr.: 01-2119491304-40	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	<i>≤</i> 2.5%
ELINCS: 400-830-7	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl) propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h- � Aquatic Chronic 2, H411;	<i>≤</i> 2.5%
EINECS: 205-480-7 Reg.nr.: 01-2119453155	n-butyl acrylate Flam. Liq. 3, H226;	<i>≤</i> 2.5%
EINECS: 201-297-1	methyl methacrylate � Flam. Liq. 2, H225; � Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<i>≤</i> 2.5%
EINECS: 203-080-7	2-ethylhexyl acrylate Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<i>≤</i> 2.5%
T.	methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	<i>≤</i> 2.5%

(Contd. on page 4)

Page 4/12

Safety data sheet

according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 07.08.2024

Trade name: C100 2K PLASTICISER GLOSS

(Contd. of page 3)

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available. · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. · 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- · 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

(Contd. on page 5)

GB

Page 5/12

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 07.08.2024

Trade name: C100 2K PLASTICISER GLOSS

See Section 13 for disposal information.

(Contd. of page 4)

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

0		5 1
1330	-20-7 xylene	
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV	
100-4	1-4 ethylbenzene	
WEL	Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk	
123-8	6-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	
141-3	2-2 n-butyl acrylate	
WEL	Short-term value: 26 mg/m³, 5 ppm Long-term value: 5 mg/m³, 1 ppm	
80-62	-6 methyl methacrylate	
WEL	Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm	
		(Contd. on page



Page 6/12

Safety data sheet

according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 07.08.2024

Trade name: C100 2K PLASTICISER GLOSS

(Contd. of page 5)

 Ingredients wi 	th biological	limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.
- · Respiratory protection: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

Page 7/12

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 07.08.2024

(Contd. of page 6)

Trade name: C100 2K PLASTICISER GLOSS

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

General Information	
Appearance: Form:	Liquid
Colour:	Liquid Colourless
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: 136 °C
Flash point:	27 °C
Flammability (solid, gas):	Flammable.
Auto-ignition temperature:	430 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
Vapour pressure at 20 °C:	6.7 hPa
Density at 20 °C:	1.0026 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.

Page 8/12

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 07.08.2024

Trade name: C100 2K PLASTICISER GLOSS

	(Contd. of pag
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	42.0 %
VÕC (EC)	420.9 g/l
Solids content:	56.3 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 9)

Page 9/12

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 07.08.2024

(Contd. of page 8)

Trade name: C100 2K PLASTICISER GLOSS

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 10)

GB

Page 10/12

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 07.08.2024

Trade name: C100 2K PLASTICISER GLOSS

(Contd. of page 9)

14.1 UN-Number ADR, IMDG, IATA	UN1263
	0101203
14.2 UN proper shipping name ADR	1262 DAINT
IMDG, IATA	1263 PAINT PAINT
14.3 Transport hazard class(es)	NOT APPLICABLE
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IĂTA	<i>III</i>
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
14.7 Transport in bulk according to Ann	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000

Page 11/12

Safety data sheet

according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 07.08.2024

Trade name: C100 2K PLASTICISER GLOSS

· UN "Model Regulation":

UN 1263 PAINT, 3, III

(Contd. of page 10)

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

(Contd. on page 12)



Page 12/12

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 07.08.2024

Trade name: C100 2K PLASTICISER GLOSS

	(Contd. of page
H373 May cause damage to organs through prolonged or repeated exposure.	
H400 Very toxic to aquatic life.	
H410 Very toxic to aquatic life with long lasting effects.	
H411 Toxic to aquatic life with long lasting effects.	
· Department issuing SDS: Product safety department	
· Contact: N/A	
Abbreviations and acronyms: Diversion of the marken descent and the marken descent and the marken descent and the former of the marken descent and them	r (Dagulationa Canaarn
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fe the International Transport of Dangerous Goods by Rail)	r (Regulations Concern
ICAO: International Civil Aviation Organisation	
ADR: Accord relatif au transport international des marchandises dangereuses par route (European A	areement Concerning
International Carriage of Dangerous Goods by Road)	greenient ooncerning
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT SE 3. Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aguatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
Aquatic Acute 1. Inazardous to the aquatic environment - acute aquatic Inazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
\cdot * Data compared to the previous version altered.	
Data compared to the previous version altered.	