



Product Description

Silicone remover is suitable for cleaning and degreasing solvent-based products. Silicone remover has a high performance with anti-static properties combined in one product, which makes it suitable for all repairs in the body shop.

Suitable Substrates:

- OEM
- Thermoplastic acrylic finishes and glass reinforced polyester parts. Suitable for degreasing all Primer surfacers prior to finishing.

Product Application



Wear suitable protection

Product Characteristics

Surface Preparation:	Prior to any repair or refinishing, wash down the vehicle to remove all external contaminants (i.e bird droppings, flies, tree sap, etc)
Raw Material:	Organic Solvents
Cleaning Techniques:	Use before sanding, apply by means of a soaked cloth and remove with a clean dry cloth. (Wipe on wipe off) Use also before applying primers and topcoats
Important remarks:	For professional use only, Do not allow silicone remover to dry on surfaces. Change cloth often
VOC(2004/42/EC):	2004/42/IIB (a) (850)800. The EU limit value for this product (product category IIB.a) in ready to use form is max 850g/ltr. The VOC content of this product in ready for use form is max. 800 g/l.
Flash Point:	21°C (70°F)
Specific Gravity:	0.77 kg/cm ³
SDS:	Refer to the Safety Data Sheet

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.