

Page 1/12

Safety data sheet according to UK REACH

Printing date 07.08.2024 Version number 1.1 Revision: 07.08.2024

SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: C060M 2K CLEAR MATT
- · Article number: C060M
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint
- · Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category

PC9a Coatings and paints, thinners, paint removers

PC9b Fillers, putties, plasters, modelling clay

- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

P.O. Box 7623

Beirut LEBANON

info@generalpaint.biz

Générale de Peinture, 70 Rue Cortambert 75116 Paris, France

Tel:+33(0)175293559

- · Further information obtainable from: Product Safety Department
- · 1.4 Emergency telephone number: +33 (0)6 07 87 13 41

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008) with its amendment Regulation (EU) 2020/878



Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)



Page 2/12

Safety data sheet according to UK REACH

Printing date 07.08.2024 Version number 1.1 Revision: 07.08.2024

Trade name: C060M 2K CLEAR MATT

(Contd. of page 1)

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-, methyl methacrylate, 2,3-epoxypropyl neodecanoate, n-butyl acrylate, methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

GB





Safety data sheet according to UK REACH

Printing date 07.08.2024 Version number 1.1 Revision: 07.08.2024

Trade name: C060M 2K CLEAR MATT

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures

| Dangerous components: | | |
|--|--|--------------------|
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32 | xylene → Flam. Liq. 3, H226; → Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | >10- <i>≤</i> 25% |
| CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29 | n-butyl acetate Tlam. Liq. 3, H226; STOT SE 3, H336 | >10- <i>≤</i> 25% |
| CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 05-2116413226-56 | 2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 | >2.5-≤10% |
| CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35 | ethylbenzene ♦ Flam. Liq. 2, H225; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♦ Acute Tox. 4, H332 | >2.5- <i>≤</i> 10% |
| CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27 | Solvent naphtha (petroleum), light arom. Acute Tox. 4, H332; STOT SE 3, H335 | <i>≤</i> 2.5% |
| CAS: 41556-26-7 Reg.nr.: 01-2119491304-40 | bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317 | <i>≤</i> 2.5% |
| CAS: 104810-47-1 ELINCS: 400-830-7 Reg.nr.: 01-0000015075-76-0017 | s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl) propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-Aquatic Chronic 2, H411; | <i>≤</i> 2.5% |
| CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28 | methyl methacrylate Tlam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 | <i>≤</i> 2.5% |
| CAS: 26761-45-5 EINECS: 247-979-2 Reg.nr.: 01-2119431597-33 | 2,3-epoxypropyl neodecanoate Acute Tox. 3, H331; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317 | <i>≤</i> 2.5% |
| CAS: 141-32-2 EINECS: 205-480-7 Reg.nr.: 01-2119453155 | n-butyl acrylate Flam. Liq. 3, H226; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 | <i>≤</i> 2.5% |



Page 4/12

Safety data sheet according to UK REACH

Printing date 07.08.2024 Version number 1.1 Revision: 07.08.2024

Trade name: C060M 2K CLEAR MATT

CAS: 82919-37-7 methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate

Aquatic Acute 1, H400; Aquatic Chronic 1, H410;

Skin Sens. 1, H317

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 5)



Page 5/12

Safety data sheet according to UK REACH

Printing date 07.08.2024 Version number 1.1 Revision: 07.08.2024

Trade name: C060M 2K CLEAR MATT

(Contd. of page 4)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage.
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk

(Contd. on page 6)



Page 6/12

Safety data sheet according to UK REACH

Printing date 07.08.2024 Version number 1.1 Revision: 07.08.2024

Trade name: C060M 2K CLEAR MATT

(Contd. of page 5)

80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

141-32-2 n-butyl acrylate

WEL Short-term value: 26 mg/m³, 5 ppm Long-term value: 5 mg/m³, 1 ppm

· Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)



Page 7/12

Safety data sheet according to UK REACH

Printing date 07.08.2024 Version number 1.1 Revision: 07.08.2024

Trade name: C060M 2K CLEAR MATT

(Contd. of page 6)

· Eye protection:



Tightly sealed goggles

| 9.1 Information on basic physical | and chemical properties |
|-----------------------------------|--|
| General Information | ana onomical proportion |
| Appearance: | |
| Form: | Liquid |
| Colour: | Clear |
| Odour: | Characteristic |
| Odour threshold: | Not determined. |
| pH-value: | Not determined. |
| Change in condition | |
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling | range: 124 °C |
| Flash point: | 25 ℃ |
| Flammability (solid, gas): | Flammable. |
| Auto-ignition temperature: | 370 ℃ |
| Decomposition temperature: | Not determined. |
| Ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product is not explosive. However, formation of explos air/vapour mixtures are possible. |
| Explosion limits: | |
| Lower: | 1.1 Vol % |
| Upper: | 7.5 Vol % |
| Vapour pressure at 20 °C: | 10.7 hPa |
| Density at 20 °C: | 1.005 g/cm³ |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| Evaporation rate | Not determined. |



according to UK REACH

Page 8/12

Printing date 07.08.2024 Version number 1.1 Revision: 07.08.2024

Trade name: C060M 2K CLEAR MATT

| | (Contd. of page 7 |
|---|--|
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: Dynamic: Kinematic: | Not determined. Not determined. |
| · Solvent content: Organic solvents: VOC (EC) | 49.2 % 494.1 g/l |
| Solids content: | 49.6 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

1330-20-7 xylene

 Oral
 LD50
 4,300 mg/kg (rat)

 Dermal
 LD50
 2,000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 9)



Page 9/12

Safety data sheet according to UK REACH

Printing date 07.08.2024 Version number 1.1 Revision: 07.08.2024

Trade name: C060M 2K CLEAR MATT

(Contd. of page 8)

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

aR .



Page 10/12

Safety data sheet according to UK REACH

Printing date 07.08.2024 Version number 1.1 Revision: 07.08.2024

Trade name: C060M 2K CLEAR MATT

(Contd. of page 9)

| 44410101 | |
|---|---|
| · 14.1 UN-Number · ADR, IMDG, IATA | UN1263 |
| · 14.2 UN proper shipping name · ADR · IMDG, IATA | 1263 PAINT PAINT |
| · 14.3 Transport hazard class(es) | NOT APPLICABLE |
| · ADR, IMDG, IATA | |
| · Class · Label | 3 Flammable liquids. 3 |
| · 14.4 Packing group · ADR, IMDG, IATA | III |
| · 14.5 Environmental hazards: · Marine pollutant: | No |
| · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category | <i>Warning: Flammable liquids.</i> 30 F-E, <u>S-E</u> A |
| · 14.7 Transport in bulk according to Annex II o Marpol and the IBC Code | f Not applicable. |
| · Transport/Additional information: | |
| · ADR · Limited quantities (LQ) · Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m |
| · Transport category · Tunnel restriction code | 3 D/E |
| · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 n |



Page 11/12

Safety data sheet according to UK REACH

Printing date 07.08.2024 Version number 1.1 Revision: 07.08.2024

Trade name: C060M 2K CLEAR MATT

(Contd. of page 10)

· UN "Model Regulation": UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

(Contd. on page 12)



Page 12/12

Safety data sheet according to UK REACH

Version number 1.1 Printing date 07.08.2024 Revision: 07.08.2024

Trade name: C060M 2K CLEAR MATT

(Contd. of page 11)

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.