



# C060M - 2K Clear Matt


## Product Description

C060M is a 2K MATT finish clearcoat. It provides an even matt uniform with no striping and no gray shade. It Matches very well with OEM Matt finishes when applied properly according to TDS instructions.

## Suitable Substrates

- Hyflow basecoat
- Hydrobase basecoat

## Product Application



	100%	50%	15-20%
C060M		H050 – FAST	S19 – FAST S11 – NORMAL S21 - SLOW
		H060 – NORMAL	
		H070 – SLOW	
		H075 – EXTRA SLOW	
		H076 - SPECIAL	



16-18 sec / DIN 4 mm / 20 °C (68 °F)  
Potlife: 3h to 5h at 20°C



HVLP 1.3 – 1.5 mm (2 spray passes)  
2.0 - 2.5 bar inlet pressure



2 Regular Coats  
50 – 60 micron



Wear suitable protection

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.



# C060M - 2K Clear Matt

## Product Characteristics

<b>VOC(2004/42/EC):</b>	2004/42/IIB (e) (840)550. The EU limit value for this product (product category IIB.e) in ready to use form is max 840g/ltr. The VOC content of this product in ready for use form is max. 550 g/l.
<b>Specific Gravity:</b>	1.01 kg/cm <sup>3</sup>
<b>Flash Point:</b>	23°C (73.4 °F)
<b>Solid Content:</b>	48% by weight pre-dilution
<b>Coverage:</b>	6-7 m <sup>2</sup> /l at 25-micron film thickness (theoretical)
<b>Gloss level:</b>	23 % ± 5 at 60° angle
<b>SDS:</b>	Refer to the Safety Data Sheet

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.