

Page 1/11


Safety data sheet

according to UK REACH

Printing date 02.08.2024

Version number 1.1

Revision: 02.08.2024





Page 2/11

Safety data sheet according to UK REACH

Printing date 02.08.2024

Version number 1.1

Revision: 02.08.2024

Trade name: P43 2K RAPID PRIMER BLACK

· Hazard pict	Contd. of page
() = () =	
	\land
<u> </u>	
	\checkmark
GHS02 G	HS07
Signal work	1 Warning
 Signal word Hazard stat 	
	nable liquid and vapour.
	es skin irritation.
	ary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition source
D0 40	No smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/heari protection.
D202, D261	
F303+F301	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse sh with water [or shower].
P501	
F301	Dispose of contents/container in accordance with local/regional/nationa international regulations.
· 2.3 Other ha	•
	PBT and vPvB assessment
· PBT: Not ap	
• vPvB: Not a	

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 1330-20-7	xylene	>10- <i>≤</i> 25%		
EINECS: 215-535-7	🚸 Flam. Lig. 3, H226; 🕔 Acute Tox. 4, H312; Acute Tox. 4,			
Reg.nr.: 01-2119486136-34	H332; Skin Irrit. 2, H315			
05-2116602925-45				
01-2119488216-32				
	(C	ontd. on page 3)		

GB –



Page 3/11

Safety data sheet according to UK REACH

Printing date 02.08.2024

Version number 1.1

Revision: 02.08.2024

Trade name: P43 2K RAPID PRIMER BLACK

	Contd. of page 2)
barium sulphate, natural substance with a Community workplace exposure limit	>10- <i>≤</i> 25%
Kaolin substance with a Community workplace exposure limit	>10- <i>≤</i> 25%
n-butyl acetate	_ >2.5-≤10%
	≤2.5%
ethylbenzene	<i>≦</i> 2.5%
dibutyltin dilaurate ♦ Acute Tox. 3, H301; ♦ Muta. 2, H341; Repr. 1B, H360FD; STOT RE 1, H372	<i>≤</i> 2.5%
	 barium sulphate, natural substance with a Community workplace exposure limit Kaolin substance with a Community workplace exposure limit n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336 Solvent naphtha (petroleum), light arom. Acute Tox. 4, H332; STOT SE 3, H335 ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332 dibutyltin dilaurate Acute Tox. 3, H301; Muta. 2, H341; Repr. 1B,

or the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 4)

GB



Page 4/11

Safety data sheet

according to UK REACH

Printing date 02.08.2024

Version number 1.1

Revision: 02.08.2024

Trade name: P43 2K RAPID PRIMER BLACK

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

(Contd. of page 3)

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3** Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly. • Information about fire - and explosion protection:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
 Storage class: 3
- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Additional information about design of technical facilities: No further data; see section 7.

Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

(Contd. on page 5)



Page 5/11

Safety data sheet according to UK REACH

Printing date 02.08.2024

Version number 1.1

Revision: 02.08.2024

Trade name: P43 2K RAPID PRIMER BLACK

7727	Contd. of pa (Contd. of pa
	Long-term value: 10* 4** mg/m ³
	*inhalable dust **respirable dust
1332	-58-7 Kaolin
WEL	Long-term value: 2 mg/m ³
123-8	86-4 n-butyl acetate
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
100-4	41-4 ethylbenzene
WEL	Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk
77-58	8-7 dibutyltin dilaurate
WEL	Short-term value: 0.2 mg/m³ Long-term value: 0.1 mg/m³ as Sn; Sk
Ingre	edients with biological limit values:
	-20-7 xylene
	V 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
Addi	itional information: The lists valid during the making were used as basis.
Pers Gene Keep Imme Wasl Avoid Avoid Resp	Exposure controls onal protective equipment: eral protective and hygienic measures: o away from foodstuffs, beverages and feed. ediately remove all soiled and contaminated clothing h hands before breaks and at the end of work. d contact with the skin. d contact with the eyes and skin. biratory protection: Not required. ection of hands:
nus Lu	Protective gloves
V	



Page 6/11

Safety data sheet

according to UK REACH

Printing date 02.08.2024

Version number 1.1

Revision: 02.08.2024

Trade name: P43 2K RAPID PRIMER BLACK

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

9.1 Information on basic physical a General Information	and chemical properties	
Appearance:		
Form:	Liquid	
Colour:	Black	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling ra	ange: 124 °C	
Flash point:	25 °C	
Flammability (solid, gas):	Flammable.	
Auto-ignition temperature:	370 °C	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	

Page 7/11

Safety data sheet according to UK REACH

Printing date 02.08.2024

Version number 1.1

Revision: 02.08.2024

Trade name: P43 2K RAPID PRIMER BLACK

	(Contd. of page 6
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
· Vapour pressure at 20 °C:	6.7 hPa
· Density at 20 °C:	1.465 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
 Solubility in / Miscibility with 	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	24.4 %
VÕC (EC)	357.7 g/l
Solids content:	75.3 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5** Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 8)

GB



Page 8/11

Safety data sheet

according to UK REACH

Printing date 02.08.2024

Version number 1.1

Revision: 02.08.2024

Trade name: P43 2K RAPID PRIMER BLACK

(Contd. of page 7)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicitv

- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

Safety data sheet

according to UK REACH

Printing date 02.08.2024

Version number 1.1

Revision: 02.08.2024

Trade name: P43 2K RAPID PRIMER BLACK

(Contd. of page 8)

Page 9/11

Uncleaned packaging:
 Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT
14.3 Transport hazard class(es)	NOT APPLICABLE
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	<i>III</i>
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number:	Warning: Flammable liquids. 30 F-E, <u>S-E</u>
Stowage Category	A
14.7 Transport in bulk according to Annex II o Marpol and the IBC Code	f Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 n
Transport category Tunnel restriction code	3 D/E
	(Contd. on page 1

Page 10/11

Safety data sheet according to UK REACH

according to UK

Printing date 02.08.2024

Version number 1.1

Revision: 02.08.2024

Trade name: P43 2K RAPID PRIMER BLACK

(Contd. of page 9)

10%

 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act

· Regulated explosives precursors

7647-01-0 hydrogen chloride

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H301 Toxic if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.

(Contd. on page 11)

GB



Page 11/11

Safety data sheet according to UK REACH

Printing date 02.08.2024

Version number 1.1

Revision: 02.08.2024

Trade name: P43 2K RAPID PRIMER BLACK

(Contd. of page 10) Harmful if inhaled. H332 H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H341 Suspected of causing genetic defects. H360FD May damage fertility. May damage the unborn child. H372 Causes damage to organs through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure. · Department issuing SDS: Product safety department · Contact: N/A · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Muta. 2: Germ cell mutagenicity – Category 2 Repr. 1B: Reproductive toxicity – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 • * Data compared to the previous version altered.