

N21 – Fiber Glass Putty Fine



Product Description

This great metal filler is the super strong long strand fiberglass filler for maximum bonding power and unparalleled strength. It is used on metal and fiberglass panels for repairs like rusted-out metal, cracked or shattered fiberglass.

Suitable Substrates:

- Iron, steel plate, glass fiber reinforced plastic
- Original paints or aged topcoat finishes

Surface Preparation:

- Sand or grind damaged area to bare metal
- Clean well the surface to be treated with S241 Genclean. Make sure it is dry and free from silicone, wax, grease and any extraneous material.
- For small holes and cracks fiberglass backing is not needed but for large holes, make sure that the fiberglass backing covers hole and extends well back about 5-10 cm into the side.

Product Application



1 – 3% Hymax hardener
Potlife 5 - 7 min at 20°C



Application with putty knife



< 30 min at 20°C



4 – 5 min at 1 m.

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.

N21 – Fiber Glass Putty Fine



Dry sanding with P36 – P80

Product Characteristics

VOC(2004/42/EC): 2004/42/II B (b) (250)250. The EU limit value for this product (product category II B.b) in ready to use form is max 250g/ltr. The VOC content of this product in ready for use form is max. 250 g/l.

Composition Unsaturated polyester resin and mineral charges

Specific Weight: 1.45 ± 0.1

Available Colors: Green.

SDS: Refer to the Safety Data Sheet.

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.