

Page 1/11


Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2024

Version number 1.1

Revision: 29.05.2024





Flammable liquid and vapour.

(Contd. on page 2)



Page 2/11

Safety data sheet


according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2024

Version number 1.1

Revision: 29.05.2024

Trade name: H020 2K HARDENER SUPER FAST





Page 3/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2024

Version number 1.1

Revision: 29.05.2024

Trade name: H020 2K HARDENER SUPER FAST

(Contd. of page 2) P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/ international regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

Composition/information on ingredients FCTION 3:

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
1330-20-7		>25- <i>≤</i> 50%	
	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315		
28182-81-2	Homopolymer of hexamethylene diisocyanate	>25- <i>≤</i> 50%	
	🚸 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335		
123-86-4	n-butyl acetate	>10- <i>≤</i> 25%	
	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336		
53880-05-0	Isophorone Diisocyanate homopolymer	>2.5- <i>≤</i> 10%	
	Resp. Sens. 1, H334; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335		
108-65-6	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%	
	🚸 Flam. Liq. 3, H226		
· Additional	• Additional information: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 4) LB/AR



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2024

Version number 1.1

Revision: 29.05.2024

(Contd. of page 3)

Page 4/11

Trade name: H020 2K HARDENER SUPER FAST

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 5)

LB/AR



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2024

Version number 1.1

Revision: 29.05.2024

Trade name: H020 2K HARDENER SUPER FAST

(Contd. of page 4)

Page 5/11

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.

· Ingredients	 Ingredients with limit values that require monitoring at the workplace: 		
1330-20-7 x	ylene		
IOELV (EU)	Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin		
123-86-4 n-l	butyl acetate		
IOELV (EU)	Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm		
108-65-6 2-1	methoxy-1-methylethyl acetate		
IOELV (EU)	Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin		
· Additional i	information: The lists valid during the making were used as basis.		
 General pro Keep away in Immediately Wash hands Avoid contact Respiratory In case of b 	rotective equipment: btective and hygienic measures: from foodstuffs, beverages and feed. remove all soiled and contaminated clothing s before breaks and at the end of work. ct with the eyes and skin. r protection: brief exposure or low pollution use respiratory filter device. In case of intensive or longer se self-contained respiratory protective device.		
PI	rotective gloves		

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. (Contd. on page 6) LB/AR-



Page 6/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2024

Version number 1.1

Revision: 29.05.2024

Trade name: H020 2K HARDENER SUPER FAST

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

9.1 Information on basic physical a General Information	and chemical properties	
Appearance:		
Form:	Liquid	
Colour:	Clear	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling ra	ange: 124 °C	
Flash point:	25 ℃	
Flammability (solid, gas):	Flammable.	
Auto-ignition temperature:	370 °C	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	

- LB/AR



Page 7/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2024

Version number 1.1

Revision: 29.05.2024

Trade name: H020 2K HARDENER SUPER FAST

	(Contd. of page 6)
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
· Density at 20 °C:	0.99652 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	60.6 %
VÕC (EC)	604.3 g/l
Solids content:	40.1 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 8)

LB/AR



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2024

Version number 1.1

Revision: 29.05.2024

Trade name: H020 2K HARDENER SUPER FAST

(Contd. of page 7)

Page 8/11

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

- · Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation
- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 9)



Page 9/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2024

Version number 1.1

Revision: 29.05.2024

Trade name: H020 2K HARDENER SUPER FAST

· 12.6 Other adverse effects No further relevant information available.

(Contd. of page 8)

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
 Recommendation
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information · 14.1 UN-Number · ADR, IMDG, IATA UN1263 · 14.2 UN proper shipping name · ADR 1263 PAINT · IMDG, IATA PAINT · 14.3 Transport hazard class(es) NOT APPLICABLE · ADR, IMDG, IATA · Class 3 Flammable liquids. · Label 3 · 14.4 Packing group · ADR, IMDG, IATA $\parallel \parallel$ · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): 30 · EMS Number: F-E,S-E · Stowage Category Α · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. (Contd. on page 10) LB/AR



Page 10/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2024

Version number 1.1

Revision: 29.05.2024

Trade name: H020 2K HARDENER SUPER FAST

· Transport/Additional information:	(Contd. of page
ADR Limited quantities (LQ) Excented guantities (EQ)	5L Code: E1
 Excepted quantities (EQ) Transport category Tunnel restriction code 	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m 3 D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU

· Relevant phrases

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H226 Flammable liquid and vapour.

(Contd. on page 11)



Page 11/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2024

Version number 1.1

Revision: 29.05.2024

Trade name: H020 2K HARDENER SUPER FAST

(Contd. of page 10) H336 May cause drowsiness or dizziness. · Department issuing SDS: Product safety department · Contact: N/A Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 * * Data compared to the previous version altered. I B/AR