

Page 1/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 1.1

Revision: 04.06.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking
· 1.1 Product identifier PRIMERS
· Trade name: <u>P62 PU PRIMER LIGHT GREY</u>
 Article number: P69 1.2 Relevant identified uses of the substance or mixture and uses advised against use as paint primer Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC9b Fillers, putties, plasters, modelling clay Application of the substance / the mixture refer to the relevant Technical Data Sheet refer to the relevant Technical Data Sheet
 1.3 Details of the supplier of the safety data sheet General Paint Co. S.A.L -Safety Department-
For further information, Please consult our Internet site www.hymax.biz • Manufacturer/Supplier: General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@generalpaint.biz Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559 info@hymax.biz
 Further information obtainable from: Product Safety Department 1.4 Emergency telephone number: During normal opening times:(961) 9 925990 /1/2 009619925990

(Contd. on page 2)



Page 2/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31


Printing date 04.06.2024

Version number 1.1

Revision: 04.06.2024

Trade name: P62 PU PRIMER LIGHT GREY

(Contd. of page 1)



(Contd. on page 3)



Page 3/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 1.1

Revision: 04.06.2024

(Contd. of page 2)

Trade name: P62 PU PRIMER LIGHT GREY

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

1330-20-7		>10- <i>≤</i> 25%
	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
123-86-4	n-butyl acetate	>2.5- <i>≤</i> 10%
	🚸 Flam. Liq. 3, H226; 🔱 STOT SE 3, H336	
108-65-6	2-methoxy-1-methylethyl acetate	<i>≤</i> 2.5%
	🚸 Flam. Liq. 3, H226	
117-84-0	dioctyl phthalate	<i>≤</i> 2.5%
	🚸 Repr. 2, H361	
100-41-4	ethylbenzene	<i>≤</i> 2.5%
	🔞 Flam. Liq. 2, H225; 🚸 STOT RE 2, H373; Asp. Tox. 1, H304; 🚸 Acute Tox. 4, H332	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

(Contd. on page 4)



Page 4/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 1.1

Revision: 04.06.2024

Trade name: P62 PU PRIMER LIGHT GREY

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 5)



Page 5/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 1.1

Revision: 04.06.2024

Trade name: P62 PU PRIMER LIGHT GREY

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see section 7.
- Ingredients with limit values that require monitoring at the workplace:

1330-20-7	xylene
-----------	--------

- IOELV (EU) Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin
- 123-86-4 n-butyl acetate
- IOELV (EU) Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm

108-65-6 2-methoxy-1-methylethyl acetate

. ,	Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm
	Skin

100-41-4 ethylbenzene

IOELV (EU) Short-term value: 884 mg/m³, 200 ppm Long-term value: 442 mg/m³, 100 ppm Skin

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.
- **Respiratory protection:** Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

LB/AR



Page 6/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 1.1

Revision: 04.06.2024

Trade name: P62 PU PRIMER LIGHT GREY

· Material of gloves

(Contd. of page 5)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

 9.1 Information on basic physical and c General Information 	mennear properties
· Appearance:	
Form:	Liquid
Colour:	Light grey
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: 124 °C
· Flash point:	25 °C
· Flammability (solid, gas):	Flammable.
Auto-ignition temperature:	370 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosi air/vapour mixtures are possible.
• Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %



Page 7/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 1.1

Revision: 04.06.2024

Trade name: P62 PU PRIMER LIGHT GREY

	(Contd. of page
· Vapour pressure at 20 °C:	6.7 hPa
· Density at 20 °C:	1.663 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	22.8 %
VÕC (EC)	379.0 g/l
Solids content:	75.3 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 xylene

- Oral LD50 4,300 mg/kg (rat)
- Dermal LD50 2,000 mg/kg (rabbit)

(Contd. on page 8)



Page 8/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 1.1

Revision: 04.06.2024

(Contd. of page 7)

Trade name: P62 PU PRIMER LIGHT GREY

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 9)



Page 9/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 1.1

Revision: 04.06.2024

Trade name: P62 PU PRIMER LIGHT GREY

(Contd. of page 8)

14.2 UN proper shipping name ADR IMDG, IATA 1263 PAINT 14.3 Transport hazard class(es) NOT APPLICABLE ADR, IMDG, IATA ADR, IMDG, IATA Image: Class and the image of t	14.1 UN-Number ADR, IMDG, IATA	UN1263
ADR 1263 PAINT IMDG, IATA PAINT 14.3 Transport hazard class(es) NOT APPLICABLE ADR, IMDG, IATA III Image: Class 3 Flammable liquids. Image: Class 30 F-E,S-E Stowage Category A A Information: F-E,S-E Marpoi and the IBC Code Not applicable. Transport/Additional information: Mot applicable. Image: Class SL Excepted quantities (LQ) SL Excepted quantities (LQ) SL Image: Class SL Image: Class SL Image: C		-
IMDG, IATA PAINT 14.3 Transport hazard class(es) NOT APPLICABLE ADR, IMDG, IATA NOT APPLICABLE Image: Stress of the st		1263 PAINT
ADR, IMDG, IATA View Class 3 Flammable liquids. Label 3 14.4 Packing group 3 ADR, IMDG, IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): 30 FMS Number: F-E,S-E Stowage Category A 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. Transport/Additional information: Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r Transport category 3 Tunnel restriction code D/E IMDG Limited quantities (LQ) 5L Excepted quantities (LQ) 5L Excepted quantities (LQ) 5L Excepted quantities (LQ) 5L IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) 5L Code: E1 Maximum net quantity per inner packaging: 30 ml	IMDG, IATA	
Class 3 Flammable liquids. Label 3 14.4 Packing group 14.4 Packing group ADR, IMDG, IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): 30 EMS Number: F-E,S-E Stowage Category A 14.7 Transport in bulk according to Annex II of Not applicable. Transport/Additional information: Not applicable. ADR Code: E1 Limited quantities (LQ) 5L Excepted quantities (EQ) 5L Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantities (LQ) 5L IMDG J/E Limited quantities (LQ) 5L Excepted quantities (LQ) 5L Excepted quantities (LQ) 5L MDG Code: E1 Maximum net quantity per inner packaging: 30 ml	14.3 Transport hazard class(es)	NOT APPLICABLE
Label314.4 Packing group ADR, IMDG, IATAIII14.5 Environmental hazards: Marine pollutant:III14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number:Warning: Flammable liquids. 30 F-E,S-E5towage CategoryA14.7 Transport in bulk according to Annex II of Marpol and the IBC CodeNot applicable.Transport/Additional information:SLADR Limited quantities (LQ)SL Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 rTransport category3Tunnel restriction codeD/EIMDG Limited quantities (LQ)SL Code: E1 Maximum net quantity per inner packaging: 1000 rTimbed quantities (LQ)SL Code: E1 Maximum net quantity per outer packaging: 1000 rTransport category3Tunnel restriction codeD/EIMDG Limited quantities (EQ)SL Code: E1 Maximum net quantity per inner packaging: 30 ml	ADR, IMDG, IATA	
Label314.4 Packing group ADR, IMDG, IATAIII14.5 Environmental hazards: Marine pollutant:III14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number:Warning: Flammable liquids. 30 F-E,S-E5towage CategoryA14.7 Transport in bulk according to Annex II of Marpol and the IBC CodeNot applicable.Transport/Additional information:Not applicable.ADR Limited quantities (LQ)5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r 3 Tunnel restriction codeIMDG Limited quantities (LQ)5L Code: E1 Maximum net quantity per inner packaging: 1000 r 3 D/EIMDG Limited quantities (LQ)5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 1000 r 3 D/E		
ADR, IMDG, IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): 30 EMS Number: F-E,S-E Stowage Category A 14.7 Transport in bulk according to Annex II of Not applicable. Marpol and the IBC Code Not applicable. Transport/Additional information: ADR Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r Transport category 3 Tunnel restriction code D/E IMDG Limited quantities (LQ) 5L Excepted quantities (LQ) 5L Excepted quantities (LQ) 5L Excepted quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml		-
Marine pollutant: No 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): 30 EMS Number: F-E,S-E Stowage Category A 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. Transport/Additional information: Not applicable. ADR Limited quantities (LQ) Excepted quantities (EQ) 5L Transport category 3 Tunnel restriction code D/E IMDG Limited quantities (LQ) 5L Limited quantities (LQ) 5L Excepted quantities (LQ) 5L Excepted quantities (LQ) 5L Imited quantities (LQ) 5L IMDG 5L Limited quantities (EQ) 5L Excepted quantities (EQ) 5L		<i>III</i>
Hazard identification number (Kemler code): 30 EMS Number: F-E,S-E Stowage Category A 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. Transport/Additional information: Not applicable. ADR SL Limited quantities (LQ) SL Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r Transport category 3 Tunnel restriction code D/E IMDG SL Limited quantities (LQ) SL Excepted quantities (LQ) SL Excepted quantities (LQ) SL IMDG SL Limited quantities (LQ) SL Excepted quantities (EQ) SL Code: E1 Maximum net quantity per inner packaging: 30 ml		No
EMS Number: F-E,S-E Stowage Category A 14.7 Transport in bulk according to Annex II of Not applicable. Marpol and the IBC Code Not applicable. Transport/Additional information: ADR Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r Transport category 3 Tunnel restriction code D/E IMDG 5L Limited quantities (LQ) 5L Excepted quantities (LQ) 5L Excepted quantities (LQ) 5L IMDG 5L Limited quantities (LQ) 5L Excepted quantities (EQ) 5L Maximum net quantity per inner packaging: 30 ml		Warning: Flammable liquids.
Stowage CategoryA14.7 Transport in bulk according to Annex II of Marpol and the IBC CodeNot applicable.Transport/Additional information:Not applicable.ADR Limited quantities (LQ)5LExcepted quantities (EQ)Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 rTransport category Tunnel restriction code3 D/EIMDG Limited quantities (LQ)5L Code: E1 Maximum net quantity per outer packaging: 1000 rIMDG Limited quantities (LQ)5L SLExcepted quantities (EQ)5L Code: E1 Maximum net quantity per inner packaging: 30 ml		
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. Transport/Additional information: ADR Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r Transport category 3 Tunnel restriction code D/E IMDG Limited quantities (LQ) 5L Excepted quantities (LQ) 5L Maximum net quantities (LQ) SL IMDG 5L Limited quantities (LQ) 5L Excepted quantities (LQ) 5L Maximum net quantity per inner packaging: 30 ml		
Marpol and the IBC Code Not applicable. Transport/Additional information: ADR ADR 5L Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r Transport category 3 Tunnel restriction code D/E IMDG 5L Limited quantities (LQ) 5L Excepted quantities (EQ) 5L Maximum net quantity per inner packaging: 30 ml Maximum net quantities (LQ) 5L IMDG 5L Limited quantities (LQ) 5L Excepted quantities (EQ) 5L Code: E1 Maximum net quantity per inner packaging: 30 ml	• • •	
Transport/Additional information: ADR Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r Transport category 3 Tunnel restriction code D/E IMDG 5L Limited quantities (LQ) 5L Excepted quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml	14.7 Transport in bulk according to Annex II o	
ADR Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r Transport category 3 Tunnel restriction code D/E IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml	•	
Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r Transport category 3 Tunnel restriction code D/E IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1		
Excepted quantities (ÉQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r Transport category 3 Tunnel restriction code D/E IMDG 5L Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml		51
Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r Transport category 3 Tunnel restriction code D/E IMDG 5L Excepted quantities (EQ) 5L Code: E1 Maximum net quantity per inner packaging: 30 ml		-
Transport category 3 Tunnel restriction code D/E IMDG 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per outer packaging: 30 ml		
Tunnel restriction codeD/EIMDG5LLimited quantities (LQ)5LExcepted quantities (EQ)Code: E1Maximum net quantity per inner packaging: 30 ml		Maximum net quantity per outer packaging: 1000 r
IMDGLimited quantities (LQ)5LExcepted quantities (EQ)Code: E1Maximum net quantity per inner packaging: 30 ml	Transport category	
Limited quantities (LQ)5LExcepted quantities (EQ)Code: E1Maximum net quantity per inner packaging: 30 ml	I unnel restriction code	D/E
Excepted quantities (ÉQ) Code: E1 Maximum net quantity per inner packaging: 30 ml		-
Maximum net quantity per inner packaging: 30 ml		
	Excepted quantities (EQ)	•••••



Page 10/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 1.1

Revision: 04.06.2024

Trade name: P62 PU PRIMER LIGHT GREY

· UN "Model Regulation":

UN 1263 PAINT, 3, III

(Contd. of page 9)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

· Department issuing SDS: Product safety department

- · Contact: N/A
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

(Contd. on page 11)

⁻ LB/AR



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 1.1

Revision: 04.06.2024

(Contd. of page 10)

Page 11/11

Trade name: P62 PU PRIMER LIGHT GREY

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 • * Data compared to the previous version altered.