



# P08 - 1K Tintable Sealer

## Product Description:

P08 is a tinted 1Klaknik car polish with a velvety smooth finish. P08 is part of the Hymax mixing system, so it is fully supplied with Hymax basecoat shades. P08 does not cause problems with delicate application.

P08 dries quickly, helps avoid scratching characteristic by half and provides color uniformity for the brown basecoat.

## Surface preparation:

- The old paint was thoroughly sanded and the surfaces were well primed and prepared.

## Suitable substrates:

- Existing finishes except TPA
- 1K or 2K "HYMAX" primers
- OEM or EDP primer, sanded
- "HYMAX" polyester putties
- Bare metal substrates must be pre-primed with P97 wash primer

## Product Application



Thinners 100% "Hymax" (as a clear sealer)

**Mix one (1) part P08 Sealer with one (1) to (2) parts B Series Tints (depending on color coverage). Thin 75% at appropriate speed with Hymax Reducer.**

Mix one (1) part P08 with one (1) part Hymax Reducer to use as a clear sealer.



18-19 sek. / DIN 4 mm / 20°C (68°F)




Compliant 1.4–1.5 mm  
2.0–2.5 bar inlet pressure  
HVLP 1.4–1.5 mm; 0.7 bar at air cap  
8–12 microns per coat

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.

## P08 - 1K Tintable Sealer



5 min. between layers.



Wait until the polish is completely matte before applying the top coat.

### Product characteristics

#### Specific Gravity

1.09 kg/cm<sup>3</sup>

#### Flash Point

27°C

#### Solid Content

42% by weight

#### Coverage

8 - 10 m<sup>2</sup>/l at a dry layer thickness of 25 microns (theoretically)

#### SDS:

Please read the safety data sheet

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.