



## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

### 1 Identification

- **Product identifier**
- **Trade name:** C090 2K PLASTICISER MATT
- **Article number:** C090
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
General Paint Co. SAL  
P.O. Box 7623  
Beirut  
LEBANON  
info@hymax.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** 1-800-535-5053 contract number (89244)

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

US

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C090 2K PLASTICISER MATT**

(Contd. of page 1)

### · Hazard pictograms



GHS02 GHS07 GHS08

### · Signal word *Warning*

### · Hazard-determining components of labeling:

ethylbenzene

2-ethylhexyl acrylate

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-

(2h-

n-butyl acrylate

methyl methacrylate

### · Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause damage to the hearing organs through prolonged or repeated exposure.

### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

(Contd. on page 3)



## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C090 2K PLASTICISER MATT**

(Contd. of page 2)

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Classification system:****NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

**HMIS-ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

**Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

### 3 Composition/information on ingredients

**Chemical characterization: Mixtures****Description:** Mixture of the substances listed below with nonhazardous additions.**Dangerous components:**

1330-20-7	xylene	>25-≤50%
123-86-4	n-butyl acetate	>10-≤25%
100-41-4	ethylbenzene	>2.5-≤10%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	≤2.5%
104810-47-1	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol- ohydroxypoly(oxyethylene);a-3-(3-(2h-	≤2.5%
141-32-2	n-butyl acrylate	≤2.5%
80-62-6	methyl methacrylate	≤2.5%
103-11-7	2-ethylhexyl acrylate	≤2.5%

US

(Contd. on page 4)



## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C090 2K PLASTICISER MATT**

(Contd. of page 3)

### 4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

- **Advice for firefighters**

- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

(Contd. on page 5)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C090 2K PLASTICISER MATT**

(Contd. of page 4)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**· Protective Action Criteria for Chemicals****· PAC-1:**

1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
100-41-4	ethylbenzene	33 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
141-32-2	n-butyl acrylate	8.3 ppm
80-62-6	methyl methacrylate	17 ppm
103-11-7	2-ethylhexyl acrylate	15 ppm
78-83-1	butanol	150 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m <sup>3</sup>

**· PAC-2:**

1330-20-7	xylene	920* ppm
123-86-4	n-butyl acetate	200 ppm
100-41-4	ethylbenzene	1100* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
141-32-2	n-butyl acrylate	130 ppm
80-62-6	methyl methacrylate	120 ppm
103-11-7	2-ethylhexyl acrylate	120 ppm
78-83-1	butanol	1,300 ppm
77-58-7	dibutyltin dilaurate	8 mg/m <sup>3</sup>

**· PAC-3:**

1330-20-7	xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm
100-41-4	ethylbenzene	1800* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
141-32-2	n-butyl acrylate	480 ppm
80-62-6	methyl methacrylate	570 ppm
103-11-7	2-ethylhexyl acrylate	150 ppm
78-83-1	butanol	8000* ppm
77-58-7	dibutyltin dilaurate	48 mg/m <sup>3</sup>

US

(Contd. on page 6)



## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C090 2K PLASTICISER MATT**

(Contd. of page 5)

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

#### 1330-20-7 xylene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

#### 123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

(Contd. on page 7)

-US-



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C090 2K PLASTICISER MATT**

(Contd. of page 6)

**100-41-4 ethylbenzene**

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

**108-65-6 2-methoxy-1-methylethyl acetate**

WEEL	Long-term value: 50 ppm
------	-------------------------

**141-32-2 n-butyl acrylate**

REL	Long-term value: 55 mg/m <sup>3</sup> , 10 ppm
TLV	Long-term value: 11 mg/m <sup>3</sup> , 2 ppm DSEN, A4

**80-62-6 methyl methacrylate**

PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 410 mg/m <sup>3</sup> , 100 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm DSEN, A4

**· Ingredients with biological limit values:****1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

**100-41-4 ethylbenzene**

BEI	0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.

(Contd. on page 8)

US

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C090 2K PLASTICISER MATT**

(Contd. of page 7)

• **Breathing equipment:**

*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.*

• **Protection of hands:**



Protective gloves

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*

• **Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

• **Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

• **Eye protection:**



Tightly sealed goggles

### 9 Physical and chemical properties

• **Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

<b>Form:</b>	Liquid
<b>Color:</b>	Colorless
<b>Odor:</b>	Characteristic
<b>Odor threshold:</b>	Not determined.

• **pH-value:** Not determined.

• **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	124 °C (255.2 °F)

(Contd. on page 9)





## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C090 2K PLASTICISER MATT**

(Contd. of page 8)

· <b>Flash point:</b>	27 °C (80.6 °F)
· <b>Flammability:</b>	Flammable.
· <b>Auto igniting:</b>	370 °C (698 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Ignition temperature:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	10.7 hPa (8 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	1.032 g/cm <sup>3</sup> (8.61204 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
Dynamic:	Not determined.
Kinematic:	Not determined.
· <b>Solvent content:</b>	
Organic solvents:	52.1 %
Coating VOC content:	52.12 %
	537.9 g/l / 4.49 lb/gal
Material VOC content:	537.9 g/l / 4.49 lb/gal
Solids content:	46.8 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.

(Contd. on page 10)

US



## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C090 2K PLASTICISER MATT**

(Contd. of page 9)

- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**1330-20-7 xylene**

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
141-32-2	n-butyl acrylate	3
80-62-6	methyl methacrylate	3
103-11-7	2-ethylhexyl acrylate	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 11)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C090 2K PLASTICISER MATT**


(Contd. of page 10)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |   |                     |
|---|---------------------|
| • <b>UN-Number</b>  | N/A                 |
| • <b>DOT, ADR, IMDG, IATA</b>   | UN1263              |
| • <b>UN proper shipping name</b>  | N/A                 |
| • <b>DOT</b>  | Paint               |
| • <b>ADR</b>  | 1263 PAINT          |
| • <b>IMDG, IATA</b>   | PAINT               |
| • <b>Transport hazard class(es)</b>   | NOT APPLICABLE      |
| • <b>DOT</b>  |                     |
|  |                     |
| • <b>Class</b>  | 3 Flammable liquids |

(Contd. on page 12)

## Safety Data Sheet


acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C090 2K PLASTICISER MATT**

(Contd. of page 11)

· <b>Label</b>	3
· <b>ADR, IMDG, IATA</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Packing group</b>	NON APPLICABILE
· <b>DOT, ADR, IMDG, IATA</b>	III
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>EMS Number:</b>	F-E, S-E
· <b>Stowage Category</b>	A
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.

(Contd. on page 13)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C090 2K PLASTICISER MATT**

(Contd. of page 12)

**· Sara****· Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

**· Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

100-41-4 ethylbenzene

141-32-2 n-butyl acrylate

80-62-6 methyl methacrylate

**· TSCA (Toxic Substances Control Act):**

1330-20-7 xylene

ACTIVE

123-86-4 n-butyl acetate

ACTIVE

100-41-4 ethylbenzene

ACTIVE

108-65-6 2-methoxy-1-methylethyl acetate

ACTIVE

41556-26-7 bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

ACTIVE

104810-47-1 s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-  
ohydroxypoly(oxyethylene);a-3-(3-(2h-

ACTIVE

141-32-2 n-butyl acrylate

ACTIVE

80-62-6 methyl methacrylate

ACTIVE

103-11-7 2-ethylhexyl acrylate

ACTIVE

82919-37-7 methyl 1,2,2,6,6pntamethyl-4-piperidyl sebacate

ACTIVE

78-83-1 butanol

ACTIVE

77-58-7 dibutyltin dilaurate

ACTIVE

**· Hazardous Air Pollutants**

1330-20-7 xylene

100-41-4 ethylbenzene

80-62-6 methyl methacrylate

**· Proposition 65****· Chemicals known to cause cancer:**

100-41-4 ethylbenzene

103-11-7 2-ethylhexyl acrylate

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

(Contd. on page 14)

US

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C090 2K PLASTICISER MATT**

(Contd. of page 13)

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D
80-62-6	methyl methacrylate	E, NL

· **TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
141-32-2	n-butyl acrylate	A4
80-62-6	methyl methacrylate	A4
77-58-7	dibutyltin dilaurate	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

ethylbenzene

2-ethylhexyl acrylate

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-

n-butyl acrylate

methyl methacrylate

· **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 15)



## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C090 2K PLASTICISER MATT**

(Contd. of page 14)

**Precautionary statements**

- Obtain special instructions before use.
  - Do not handle until all safety precautions have been read and understood.
  - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
  - Keep container tightly closed.
  - Ground/bond container and receiving equipment.
  - Use explosion-proof electrical/ventilating/lighting/equipment.
  - Use only non-sparking tools.
  - Take precautionary measures against static discharge.
  - Do not breathe dust/fume/gas/mist/vapors/spray.
  - Wash thoroughly after handling.
  - Contaminated work clothing must not be allowed out of the workplace.
  - Wear protective gloves/protective clothing/eye protection/face protection.
  - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
  - If exposed or concerned: Get medical advice/attention.
  - Specific treatment (see on this label).
  - Get medical advice/attention if you feel unwell.
  - Take off contaminated clothing and wash it before reuse.
  - If skin irritation or rash occurs: Get medical advice/attention.
  - Wash contaminated clothing before reuse.
  - In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.
  - Store in a well-ventilated place. Keep cool.
  - Store locked up.
  - Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** Product safety department

• **Contact:** N/A

• **Date of preparation / last revision** 05/07/2025 / 1.0

• **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)

(Contd. on page 16)

US



## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C090 2K PLASTICISER MATT**

(Contd. of page 15)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Skin Irritation 2: Skin corrosion/irritation – Category 2

Sensitization - Skin 1: Skin sensitisation – Category 1

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

**\* Data compared to the previous version altered.**

US