

Page 1/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/28/2025

Reviewed on 01/28/2025

#### 1 Identification

- · Product identifier
- · Trade name: S241 GENCLEAN
- · Article number: S241
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

General Paint Co. SAL

P.O. Box 7623

Beirut

LEBANON

info@hymax.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

#### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B

H340 May cause genetic defects.

Carcinogenicity 1B

H350 May cause cancer.

Specific Target Organ Toxicity - Repeated Exposure H372 Causes damage to the central nervous

system through prolonged or repeated

exposure.

Aspiration Hazard 1

H304 May be fatal if swallowed and enters

airways.



Skin Irritation 2

H315 Causes skin irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



Page 2/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/28/2025 Reviewed on 01/28/2025

Trade name: S241 GENCLEAN

(Contd. of page 1)

#### · Hazard pictograms







GHS02 GHS07 GHS08

#### · Signal word Danger

#### · Hazard-determining components of labeling:

Naphtha (petroleum), hydrotreated heavy

Naphtha (petroleum), hydrodesulfurized heavy

#### · Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

May cause genetic defects.

May cause cancer.

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)



Page 3/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/28/2025 Reviewed on 01/28/2025

Trade name: S241 GENCLEAN

(Contd. of page 2)

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 1 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = \*1 Fire = 3 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
64742-48-9	Naphtha (petroleum), hydrotreated heavy	>50-≤100%
1330-20-7	*	>10-≤25%
	propan-2-ol	>2.5- <i>≤</i> 10%
123-86-4	n-butyl acetate	>2.5-≤10%
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	>2.5- <i>≤</i> 10%
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5-≤10%

#### 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)



Page 4/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/28/2025 Reviewed on 01/28/2025

Trade name: S241 GENCLEAN

(Contd. of page 3)

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:		
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m³
1330-20-7	xylene	130 ppm
67-63-0	propan-2-ol	400 ppm
123-86-4	n-butyl acetate	5 ppm
PAC-2:		
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m³
1330-20-7	xylene	920* ppm
	·	(Contd. on page 5

US



Page 5/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/28/2025 Reviewed on 01/28/2025

Trade name: S241 GENCLEAN

	propan-2-ol n-butyl acetate	(Contd. of page 4) 2000* ppm 200 ppm
· PAC-3:		10000
1330-20-7	Naphtha (petroleum), hydrotreated heavy xylene	40,000 mg/m³ 2500* ppm
	propan-2-ol n-butyl acetate	12000** ppm 3000* ppm

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

#### 1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

(Contd. on page 6)



Page 6/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/28/2025 Reviewed on 01/28/2025

Trade name: S241 GENCLEAN

(Contd. of page 5) REL Short-term value: 655 mg/m<sup>3</sup>, 150 ppm Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 20 ppm BEI, A4 67-63-0 propan-2-ol PEL Long-term value: 980 mg/m³, 400 ppm REL Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm TLV Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4 123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 950 mg/m<sup>3</sup>, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV Short-term value: 150 ppm Long-term value: 50 ppm Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids 67-63-0 propan-2-ol BEI 40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

(Contd. on page 7)



Page 7/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/28/2025 Reviewed on 01/28/2025

Trade name: S241 GENCLEAN

(Contd. of page 6)

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

#### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Color: According to product description

Odor: CharacteristicOdor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:82 °C (179.6 °F)

(Contd. on page 8)



Page 8/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/28/2025 Reviewed on 01/28/2025

Trade name: S241 GENCLEAN

	(Contd. of pag
Flash point:	24 °C (75.2 °F)
Flammability:	Flammable.
Auto igniting:	240 °C (464 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	7 Vol %
Vapor pressure at 20 °C (68 °F):	6.7 hPa (5 mm Hg)
Density at 20 °C (68 °F):	0.80735 g/cm³ (6.73734 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water	<b>er):</b> Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	100.0 %
Coating VOC content:	100.00 %
	807.3 g/l / 6.74 lb/gal
Material VOC content:	807.3 g/l / 6.74 lb/gal
Other information	No further relevant information available.

#### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 9)



Page 9/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/28/2025 Reviewed on 01/28/2025

Trade name: S241 GENCLEAN

(Contd. of page 8)

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

LD/LC50 values that are relevant for classification:

#### 64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral LD50 >5,000 mg/kg (rat)
Dermal LD50 >3,000 mg/kg (rab)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
1330-20-7	xylene	3
67-63-0	propan-2-ol	3
· NTP (Natio	onal Toxicology Program)	
None of the	e ingredients is listed.	
· OSHA-Ca	(Occupational Safety & Health Administration)	
None of the	e ingredients is listed.	

#### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 10)



Page 10/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/28/2025 Reviewed on 01/28/2025

Trade name: S241 GENCLEAN

(Contd. of page 9)

- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

· Class

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADR, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint	
ADR	1263 PAINT	
IMDG, IATA	PAINT	
Transport hazard class(es)	NOT APPLICABLE	
DOT		

3 Flammable liquids

(Contd. on page 11)



Page 11/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/28/2025 Reviewed on 01/28/2025

Trade name: S241 GENCLEAN

	(Contd. of page
Label	3
ADR, IMDG, IATA	
· Class · Label	3 Flammable liquids 3
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards: · Marine pollutant:	No
<ul> <li>Special precautions for user</li> <li>Hazard identification number (Kemler co</li> <li>EMS Number:</li> <li>Stowage Category</li> </ul>	Warning: Flammable liquids d <b>e):</b> 30 F-E, <u>S-E</u> A
· Transport in bulk according to Annex II o MARPOL73/78 and the IBC Code	of Not applicable.
· Transport/Additional information: · DOT · Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
· UN "Model Regulation":	UN 1263 PAINT, 3, III

US



HYMAX

Page 12/14

Safety Data Sheet acc. to OSHA HCS
Printing date 01/28/2025

Reviewed on 01/28/2025

Trade name: S241 GENCLEAN

(Contd. of page 11)

Safety, health and environmental regulations/legislation specific for the substance or mixture		
Sara Section 35	5 (extremely hazardous substances):	
	ingredients is listed.	
Section 31	3 (Specific toxic chemical listings):	
1330-20-7		
67-63-0	propan-2-ol	
TSCA (Tox	ic Substances Control Act):	
64742-48-9	Naphtha (petroleum), hydrotreated heavy	ACTIV
1330-20-7	xylene	ACTIV
67-63-0	propan-2-ol	ACTIV
123-86-4	n-butyl acetate	ACTIV
Hazardous	Air Pollutants	
1330-20-7	xylene	
Propositio	1 65	
Chemicals	known to cause cancer:	
None of the	ingredients is listed.	
Chemicals	known to cause reproductive toxicity for females	s:
None of the	ingredients is listed.	
Chemicals	known to cause reproductive toxicity for males:	
None of the	ingredients is listed.	
Chemicals	known to cause developmental toxicity:	
	ingredients is listed.	
Carcinogo	nic categories	
_	onmental Protection Agency)	
1330-20-7	,	
	hold Limit Value)	
		I A
1330-20-71	•	
1330-20-7 67-63-0	propan-2-ol	I A



Page 13/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/28/2025 Reviewed on 01/28/2025

Trade name: S241 GENCLEAN

(Contd. of page 12)

#### · Hazard pictograms







GHS02 GHS07 GHS08

#### · Signal word Danger

#### · Hazard-determining components of labeling:

Naphtha (petroleum), hydrotreated heavy

Naphtha (petroleum), hydrodesulfurized heavy

#### · Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

May cause genetic defects.

May cause cancer.

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 14)



Page 14/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/28/2025 Reviewed on 01/28/2025

Trade name: S241 GENCLEAN

(Contd. of page 13)

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 01/28/2025 / 1.0
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids - Category 3

Skin Irritation 2: Skin corrosion/irritation - Category 2

Germ Cell Mutagenicity 1B: Germ cell mutagenicity - Category 1B

Carcinogenicity 1B: Carcinogenicity - Category 1B

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) - Category 1

Aspiration Hazard 1: Aspiration hazard - Category 1

\* Data compared to the previous version altered.

US