



Product Description

Silicone remover is suitable for cleaning and degreasing solvent-based products. Silicone remover has a high performance with anti-static properties combined in one product, which makes it suitable for all repairs in the bodyshop.

Suitable Substrates:

- OEM
- Thermoplastic acrylic finishes and glass reinforced polyester parts. Suitable for degreasing all Primer surfacers prior to finishing.

Product Application



Wear suitable protection

Product Characteristics

Surface Preparation:

Prior to any repair or refinishing, wash down the vehicle to remove all external contaminants (i.e bird droppings, flies, tree sap, etc)

Raw Material:

Organic Solvents

Cleaning Techniques:

Use before sanding, apply by means of a soaked cloth and remove with a clean dry cloth.
(Wipe on wipe off)
Use also before applying primers and topcoats

Important remarks:

For professional use only,
Do not allow silicone remover to dry on surfaces.
Change cloth often

VOC(2004/42/EC):

2004/42/IIB (a) (850)800. The EU limit value for this product (product category IIB.a) in ready to use form is max 850g/ltr. The VOC content of this product in ready for use form is max. 800 g/l.

Flash Point:

21°C (70°F)

Specific Gravity:

0.77 kg/cm³

SDS:

Refer to the Safety Data Sheet

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.