

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

### 1 Identification

- **Product identifier**
- **Trade name:** C070LV ULTRA PERFORMANCE CLEAR
- **Article number:** C070LV
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
General Paint Co. SAL  
P.O. Box 7623  
Beirut  
LEBANON  
info@hymax.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** 1-800-535-5053 contract number (89244)

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3 H226 Flammable liquid and vapor.



GHS07

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning
- **Hazard-determining components of labeling:**  
tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate  
bis(4-(1,2-bis(ethoxycarbonyl)ethy-lamino)-3-methylcyclohexyl)methane

(Contd. on page 2)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C070LV ULTRA PERFORMANCE CLEAR**

(Contd. of page 1)

s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

**Hazard statements**

Flammable liquid and vapor.

May cause an allergic skin reaction.

**Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Classification system:****NFPA ratings (scale 0 - 4)**

Health = 0

Fire = 3

Reactivity = 0

**HMIS-ratings (scale 0 - 4)**

Health = 0

Fire = 3

Reactivity = 0

**Other hazards****Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

US

(Contd. on page 3)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C070LV ULTRA PERFORMANCE CLEAR**

(Contd. of page 2)

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

136210-30-5	tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate	>50-≤100%
136210-32-7	bis(4-(1,2-bis(ethoxycarbonyl)ethy-lamino)-3-methylcyclohexyl)methane	>10-≤25%
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5-≤10%
141-78-6	ethyl acetate	>2.5-≤10%
1330-20-7	xylene	>2.5-≤10%
123-86-4	n-butyl acetate	>2.5-≤10%
623-91-6	diethyl fumarate	>2.5-≤10%
104810-47-1	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-	≤2.5%
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	≤2.5%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C070LV ULTRA PERFORMANCE CLEAR**

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

**PAC-1:**

141-78-6	ethyl acetate	1,200 ppm
1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
122-99-6	2-phenoxyethanol	1.5 ppm
556-67-2	octamethylcyclotetrasiloxane	360 mg/m3
70657-70-4	2-methoxypropyl acetate	50 ppm

**PAC-2:**

141-78-6	ethyl acetate	1,700 ppm
1330-20-7	xylene	920* ppm
123-86-4	n-butyl acetate	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
122-99-6	2-phenoxyethanol	16 ppm
556-67-2	octamethylcyclotetrasiloxane	530 mg/m3
70657-70-4	2-methoxypropyl acetate	1,000 ppm

**PAC-3:**

141-78-6	ethyl acetate	10000** ppm
1330-20-7	xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm

(Contd. on page 5)



## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C070LV ULTRA PERFORMANCE CLEAR**

122-99-6	2-phenoxyethanol	(Contd. of page 4) 97 ppm
556-67-2	octamethylcyclotetrasiloxane	1600 mg/m <sup>3</sup>
70657-70-4	2-methoxypropyl acetate	5,000 ppm

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

#### 141-78-6 ethyl acetate

PEL	Long-term value: 1400 mg/m <sup>3</sup> , 400 ppm
REL	Long-term value: 1400 mg/m <sup>3</sup> , 400 ppm
TLV	Long-term value: 1440 mg/m <sup>3</sup> , 400 ppm

#### 1330-20-7 xylene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm

(Contd. on page 6)

US

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C070LV ULTRA PERFORMANCE CLEAR**

(Contd. of page 5)

TLV	Long-term value: 20 ppm BEI, A4
<b>123-86-4 n-butyl acetate</b>	
PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm
<b>Ingredients with biological limit values:</b>	
<b>1330-20-7 xylene</b>	
BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

• **Additional information:** The lists that were valid during the creation were used as basis.

• **Exposure controls**

• **Personal protective equipment:**

• **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.

• **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C070LV ULTRA PERFORMANCE CLEAR**

(Contd. of page 6)

**· Eye protection:**

Tightly sealed goggles

### 9 Physical and chemical properties

**· Information on basic physical and chemical properties****· General Information****· Appearance:**

<b>Form:</b>	Liquid
<b>Color:</b>	Clear
<b>Odor:</b>	Characteristic
<b>Odor threshold:</b>	Not determined.

**· pH-value:** Not determined.**· Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	77 °C (170.6 °F)

**· Flash point:** 24 °C (75.2 °F)**· Flammability:** Flammable.**· Auto igniting:** 370 °C (698 °F)**· Decomposition temperature:** Not determined.**· Ignition temperature:** Product is not selfigniting.**· Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.**· Explosion limits:**

<b>Lower:</b>	1 Vol %
<b>Upper:</b>	7.5 Vol %

**· Vapor pressure at 20 °C (68 °F):** 10.7 hPa (8 mm Hg)**· Density at 20 °C (68 °F):** 1.05 g/cm<sup>3</sup> (8.76225 lbs/gal)**· Relative density** Not determined.**· Vapor density** Not determined.**· Evaporation rate** Not determined.

(Contd. on page 8)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C070LV ULTRA PERFORMANCE CLEAR**

(Contd. of page 7)

- |   |  |  |
|---|--|--|
| · <b>Solubility in / Miscibility with Water:</b>                  |  | Not miscible or difficult to mix.          |
| · <b>Partition coefficient (n-octanol/water):</b> Not determined. |  |  |
| · <b>Viscosity:</b>   |  |  |
| <b>Dynamic:</b>   |  | Not determined.                            |
| <b>Kinematic:</b>   |  | Not determined.                            |
| · <b>Solvent content:</b>   |  |  |
| <b>Organic solvents:</b>  |  | 23.0 %                                     |
| <b>Coating VOC content:</b>                                       |  | 23.02 %                                    |
|   |  | 241.7 g/l / 2.02 lb/gal                    |
| <b>Material VOC content:</b>                                      |  | 241.7 g/l / 2.02 lb/gal                    |
| · <b>Solids content:</b>  |  | 76.2 %                                     |
| · <b>Other information</b>  |  | No further relevant information available. |

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.

(Contd. on page 9)

US





## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C070LV ULTRA PERFORMANCE CLEAR**

(Contd. of page 8)

- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7 xylene

3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2025



Reviewed on 05/07/2025

**Trade name: C070LV ULTRA PERFORMANCE CLEAR**

(Contd. of page 9)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |   |                            |
|---|----------------------------|
| · <b>UN-Number</b>  | N/A                        |
| · <b>DOT, ADR, IMDG, IATA</b>   | UN1263                     |
| · <b>UN proper shipping name</b>  | N/A                        |
| · <b>DOT</b>  | Paint                      |
| · <b>ADR</b>  | 1263 PAINT                 |
| · <b>IMDG, IATA</b>   | PAINT                      |
| · <b>Transport hazard class(es)</b>   | NOT APPLICABLE             |
| · <b>DOT</b>  |                            |
|  |                            |
| · <b>Class</b>  | 3 Flammable liquids        |
| · <b>Label</b>  | 3                          |
| <hr/>   |                            |
| · <b>ADR, IMDG, IATA</b>  |                            |
|  |                            |
| · <b>Class</b>  | 3 Flammable liquids        |
| · <b>Label</b>  | 3                          |
| · <b>Packing group</b>  | NON APPLICABLE             |
| · <b>DOT, ADR, IMDG, IATA</b>   | III                        |
| · <b>Environmental hazards:</b>   |                            |
| · <b>Marine pollutant:</b>  | No                         |
| · <b>Special precautions for user</b>   | Warning: Flammable liquids |
| · <b>Hazard identification number (Kemler code):</b>                                | 30                         |
| · <b>EMS Number:</b>  | F-E, S-E                   |
| · <b>Stowage Category</b>   | A                          |
| · <b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>   | Not applicable.            |

(Contd. on page 11)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C070LV ULTRA PERFORMANCE CLEAR**

(Contd. of page 10)

**· Transport/Additional information:****· DOT****· Quantity limitations**

On passenger aircraft/rail: 60 L  
On cargo aircraft only: 220 L

**· ADR****· Excepted quantities (EQ)**

Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

**· IMDG****· Limited quantities (LQ)****· Excepted quantities (EQ)**

5L  
Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

**· UN "Model Regulation":**

UN 1263 PAINT, 3, III

### 15 Regulatory information

**· Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

**· Sara****· Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

**· Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
122-99-6	2-phenoxyethanol
104-68-7	Diethylene glycol monophenyl ether

**· TSCA (Toxic Substances Control Act):**

136210-30-5	tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate	ACTIVE
136210-32-7	bis(4-(1,2-bis(ethoxycarbonyl)ethoxyamino)-3-methylcyclohexyl)methane	ACTIVE
141-78-6	ethyl acetate	ACTIVE
1330-20-7	xylene	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
623-91-6	diethyl fumarate	ACTIVE
104810-47-1	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-	ACTIVE
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	ACTIVE

(Contd. on page 12)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C070LV ULTRA PERFORMANCE CLEAR**

(Contd. of page 11)

82919-37-7	methyl 1,2,2,6,6,6-pentamethyl-4-piperidyl sebacate	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
122-99-6	2-phenoxyethanol	ACTIVE
104-68-7	Diethylene glycol monophenyl ether	ACTIVE
556-67-2	octamethylcyclotetrasiloxane	ACTIVE

**· Hazardous Air Pollutants**

1330-20-7	xylene
-----------	--------

**· Proposition 65****· Chemicals known to cause cancer:**

None of the ingredients is listed.
------------------------------------

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.
------------------------------------

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.
------------------------------------

**· Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.
------------------------------------

**· Carcinogenic categories****· EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
-----------	--------	---

**· TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
-----------	--------	----

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.
------------------------------------

**· GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

**· Hazard pictograms**

GHS02 GHS07

**· Signal word** Warning**· Hazard-determining components of labeling:**tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate  
bis(4-(1,2-bis(ethoxycarbonyl)ethy-lamino)-3-methylcyclohexyl)methane

(Contd. on page 13)

US



## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C070LV ULTRA PERFORMANCE CLEAR**

(Contd. of page 12)

s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

**Hazard statements**

Flammable liquid and vapor.

May cause an allergic skin reaction.

**Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Department issuing SDS:** Product safety department

**Contact:** N/A

**Date of preparation / last revision** 05/07/2025 / 1.0

**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 14)



## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2025

Reviewed on 05/07/2025

**Trade name: C070LV ULTRA PERFORMANCE CLEAR**

(Contd. of page 13)

LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
BEI: Biological Exposure Limit  
Flammable Liquids 3: Flammable liquids – Category 3  
Sensitization - Skin 1: Skin sensitisation – Category 1  
• **\* Data compared to the previous version altered.**

US