

C023 - Easy Clear




Product Description

C023 is an easy to apply high solid clearcoat with its ultimate flow and durable gloss. It is mainly suggested for fast-hand painters.

Suitable Substrates

- Hyflow basecoat


Product Application



100% Clear	50% Hardener	5-10% Thinner
C023	H070 SLOW	S21 SLOW
	H060 NORMAL	S11 NORMAL
	H070 SLOW	S19 FAST



15-16s / DIN 4 mm / 20°C



HVLP 1.3 – 1.4 mm(2 coats)
0.7 bar atomization pressure
1 medium + full coat
50 µm



Flash off 2-3 minutes between coats
10 minutes before low bake
Low Bake 20 min at 60°C panel temperature



Short Wave 10-15 min
Panel > 80cm from IR unit

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.

C023 - Easy Clear



Wear suitable protection

Product Characteristics

Specific Gravity: 0.985 kg/cm³

Flash Point: 25°C (77°F)

Solid Content: 46.2 % by weight

Coverage: 8 - 9 m²/l at 50-micron dry film thickness (theoretical)

SDS: Refer to the Safety Data Sheet

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.