

Page 1/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

1 Identification

- · Product identifier
- Trade name: <u>W210 LUMINOUS GREEN</u>
- · Article number: W210
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

• *Manufacturer/Supplier:* General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@hymax.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

Classification of the substance or mixture
 Flammable liquids 4 H227 Combustible liquid.

· Label elements

- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements Combustible liquid.
- Processionery state
- · Precautionary statements

Keep away from flames and hot surfaces. – No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)



(Contd. on page 2)

acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Trade name: W210 LUMINOUS GREEN

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:
- 111-76-2 2-butoxyethanol
- 67-63-0 propan-2-ol

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Not required. • Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

US



>2.5-*≤*10%

*≤*2.5%

The second se
HYMAX
ARTEMPTITE REFIRER

Page 2/10

(Contd. of page 1)



acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Page 3/10

Trade name: W210 LUMINOUS GREEN (Contd. of page 2) · Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. · Reference to other sections No dangerous substances are released. See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. · Protective Action Criteria for Chemicals · PAC-1: 111-76-2 2-butoxyethanol 60 ppm 67-63-0 propan-2-ol 400 ppm 108-01-0 2-dimethylaminoethanol 3.7 ppm 104-76-7 2-Ethyl-1-hexanol 0.1 ppm 140-88-5 ethyl acrylate 8.3 ppm · PAC-2: 111-76-2 2-butoxyethanol 120 ppm 2000* ppm 67-63-0 propan-2-ol 108-01-0 2-dimethylaminoethanol 12 ppm 104-76-7 2-Ethyl-1-hexanol 100 ppm 140-88-5 ethyl acrylate 36 ppm · PAC-3: 111-76-2 2-butoxyethanol 700 ppm 12000** ppm 67-63-0 propan-2-ol 108-01-0 2-dimethylaminoethanol 72 ppm 104-76-7 2-Ethyl-1-hexanol 200 ppm 140-88-5 ethyl acrylate 240 ppm

7 Handling and storage

· Handling:

· Precautions for safe handling No special precautions are necessary if used correctly.

· Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: None.

(Contd. on page 4)

US

acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Trade name: W210 LUMINOUS GREEN

· Storage class: 10

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters

	ponents with limit values that require monitoring at the workplace:
	76-2 2-butoxyethanol
	Long-term value: 240 mg/m³, 50 ppm Skin
REL	Long-term value: 24 mg/m³, 5 ppm Skin
TLV	Long-term value: 97 mg/m³, 20 ppm BEI, A3
67-6	3-0 propan-2-ol
PEL	Long-term value: 980 mg/m³, 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV	Short-term value: 984 mg/m³, 400 ppm Long-term value: 491 mg/m³, 200 ppm BEI, A4
· Ingre	edients with biological limit values:
111-	76-2 2-butoxyethanol
	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)
	3-0 propan-2-ol
BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
· Addi	itional information: The lists that were valid during the creation were used as basis.
· Pers · Gene	osure controls onal protective equipment: eral protective and hygienic measures: Wash hands before breaks and at the end of work. thing equipment: Not required.
	(Contd. on page 5)

Page 4/10

(Contd. of page 3)

US



Page 5/10

(Contd. of page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Trade name: W210 LUMINOUS GREEN

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

General Information		
· Appearance: Form: Color:	Fluid	
· Odor: · Odor threshold:	According to product description Characteristic Not determined.	
· pH-value at 20 °C (68 °F):	7.4-8.4	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 100 °C (212 °F)	
· Flash point:	68 °C (154.4 °F)	
· Flammability:	Not applicable.	
· Auto igniting:	240 °C (464 °F)	
· Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	

- US

acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Trade name: W210 LUMINOUS GREEN

	(Contd. of page
Danger of explosion:	Not determined.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
Density at 20 °C (68 °F):	1.06 g/cm³ (8.8457 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	8.0 %
Water:	66.2 %
Coating VOC content:	7.96 %
-	282.4 g/l / 2.36 lb/gal
Material VOC content:	84.3 g/l / 0.70 lb/gal
Solids content:	24.4 %
	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

US

Page 6/10

acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Trade name: W210 LUMINOUS GREEN

(Contd. of page 6)

Page 7/10

· LD/LC50	values tha	at are relevant for classification:	
111-76-2	2-butoxye	thanol	
Oral	LD50	1,200 mg/kg (ATE)	
		1,480 mg/kg (rat)	
		400 mg/kg (rab)	
Inhalative	LC50/4 h	3 mg/l (ATE)	
 on the ey Sensitiza Additional 	tion: No irritation tion: No se al toxicolog	ensitizing effects known. gical information:	
• on the ey • Sensitiza • Additiona • Carcinog	e: No irritat tion: No se al toxicolog enic categ	and effect. ensitizing effects known. gical information: gories	
 on the ey Sensitiza Additiona Carcinog IARC (Int 	re: No irrita tion: No se al toxicolo enic categ ernational	and offect. ensitizing effects known. ogical information: gories I Agency for Research on Cancer)	
 on the ey Sensitiza Additiona Carcinog IARC (Int 111-76-2 	re: No irritan tion: No se al toxicolog enic categ ernational 2-butoxyet	ating effect. ensitizing effects known. ogical information: gories I Agency for Research on Cancer) othanol	
 on the ey Sensitiza Additiona Carcinog IARC (Int 111-76-2 67-63-0 	re: No irrita tion: No se al toxicolo enic categ ernational	aning effect. ensitizing effects known. ogical information: gories I Agency for Research on Cancer) othanol	

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 8)

US

acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Trade name: W210 LUMINOUS GREEN

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

UN-Number	NOT APPLICABLE
UN proper shipping name	N/A NOT APPLICABLE
Transport hazard class(es)	NOT APPLICABLE NOT APPLICABLE
Packing group	NON APPLICABILE NOT APPLICABLE
Environmental hazards: Marine pollutant:	No
Special precautions for user	Not applicable.

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

- · Section 355 (extremely hazardous substances):
- None of the ingredients is listed.

(Contd. on page 9)



(Contd. of page 7)

Page 8/10



Page 9/10

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Trade name: W210 LUMINOUS GREEN

Section 3	13 (Specific toxic chemical listings):	
	2-butoxyethanol	
-	propan-2-ol	
140-88-5	ethyl acrylate	
· TSCA (To	xic Substances Control Act):	
	water, distilled, conductivity or of similar purity	ACTIV
	2-butoxyethanol	ACTIV
	propan-2-ol	ACTIV
	2-dimethylaminoethanol	ACTIV
	2-Ethyl-1-hexanol	ACTIV
	ethyl acrylate	ACTIV
	s Air Pollutants	
	ethyl acrylate	
· Propositio		
	s known to cause cancer:	
140-88-5	ethyl acrylate	
· Chemicals	s known to cause reproductive toxicity for females:	
None of th	e ingredients is listed.	
· Chemicals	s known to cause reproductive toxicity for males:	
None of th	e ingredients is listed.	
· Chemicals	s known to cause developmental toxicity:	
None of th	e ingredients is listed.	
· Carcinoge	enic categories	
-	ronmental Protection Agency)	
111-76-2	2-butoxyethanol	N
· TLV (Thre	shold Limit Value)	
	2-butoxyethanol	A
67-63-0	propan-2-ol	A
140-88-5	ethyl acrylate	A
· NIOSH-Ca	(National Institute for Occupational Safety and Health)	
140-88-5	ethyl acrylate	
	ct is classified and labeled according to the Globally Harmonized System (GHS c tograms Void	;).
		ontd. on page



Page 10/10

(Contd. of page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Trade name: W210 LUMINOUS GREEN

· Hazard statements Combustible liquid.

Precautionary statements
 Keep away from flames and hot surfaces. – No smoking.
 Wear protective gloves/protective clothing/eye protection/face protection.
 In case of fire: Use CO2, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 05/08/2025 / 1.0
- Abbreviations and acronyms:

EINECS: European Inventory of Éxisting Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- BEI: Biological Exposure Limit
- Flammable liquids 4: Flammable liquids Category 4
- * Data compared to the previous version altered.