

Page 1/11

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

1 Identification

- · Product identifier
- · Trade name: W810 CARBON BLACK
- · Article number: W810
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

• *Manufacturer/Supplier:* General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@hymax.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture



Eye Irritation 2A H319 Causes serious eye irritation.

Flammable liquids 4 H227 Combustible liquid.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- Hazard statements
 Combustible liquid.
 Causes serious eye irritation.
- · Precautionary statements

Keep away from flames and hot surfaces. – No smoking. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

US




acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Page 2/11

Trade name: W810 CARBON BLACK



· vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

111-76-2	2-butoxyethanol
----------	-----------------

67-63-0 propan-2-ol

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

>2.5-*≤*10%

*≤*2.5%

US



acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Trade name: W810 CARBON BLACK

- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Not required.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• **Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

· Reference to other sections

No dangerous substances are released.

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

· PAC-1:		
111-76-2	2-butoxyethanol	60 ppm
	propan-2-ol	400 ppm
	2-dimethylaminoethanol	3.7 ppm
	2-Ethyl-1-hexanol	0.1 ppm
140-88-5	ethyl acrylate	8.3 ppm
· PAC-2:		
	2-butoxyethanol	120 ppm
	propan-2-ol	2000* ppm
	2-dimethylaminoethanol	12 ppm
104-76-7	2-Ethyl-1-hexanol	100 ppm
	(C	ontd. on page 4)

(Contd. of page 2)

Page 3/11

5

Page 4/11

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Trade name: W810 CARBON BLACK

140-88-5	ethyl acrylate	(Contd. of page 3) 36 ppm
· PAC-3:		
	2-butoxyethanol	700 ppm
	propan-2-ol	12000** ppm
	2-dimethylaminoethanol	72 ppm
	2-Ethyl-1-hexanol	200 ppm
140-88-5	ethyl acrylate	240 ppm

7 Handling and storage

· Handling:

- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanolPELLong-term value: 240 mg/m³, 50 ppmSkinRELLong-term value: 24 mg/m³, 5 ppmSkinTLVLong-term value: 97 mg/m³, 20 ppm

BEI, A3

67-63-0 propan-2-ol

PEL Long-term value: 980 mg/m³, 400 ppm

(Contd. on page 5)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Page 5/11

Trade name: W810 CARBON BLACK

be checked prior to the application.

	(Contd. of page 4
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV	Short-term value: 984 mg/m³, 400 ppm Long-term value: 491 mg/m³, 200 ppm BEI, A4
· Ingr	edients with biological limit values:
111-	76-2 2-butoxyethanol
BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)
67-6	3-0 propan-2-ol
	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
· Add	itional information: The lists that were valid during the creation were used as basis.
· Gen Keep Imm Was Avoi Avoi • Brea	conal protective equipment: eral protective and hygienic measures: o away from foodstuffs, beverages and feed. ediately remove all soiled and contaminated clothing. h hands before breaks and at the end of work. d contact with the eyes. d contact with the eyes and skin. hthing equipment: Not required. ection of hands:
111 L	Protective gloves
Due prep	glove material has to be impermeable and resistant to the product/ the substance/ the preparation to missing tests no recommendation to the glove material can be given for the product/ th aration/ the chemical mixture. ction of the glove material on consideration of the penetration times, rates of diffusion and th

(Contd. on page 6) US

acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Trade name: W810 CARBON BLACK

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

General Information		
Appearance:		
Form: Color:	Fluid	
Odor:	According to product description	
Odor: Odor threshold:	Characteristic Not determined.	
pH-value at 20 °C (68 °F):	7.4-8.4	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	68 °C (154.4 °F)	
Flammability:	Not applicable.	
Auto igniting:	240 °C (464 °F)	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.01 g/cm³ (8.42845 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	

Page 6/11



(Contd. of page 5)

acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Page 7/11

US

Trade name: W810 CARBON BLACK

	(Contd. of	f page
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/	water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	11.1 %	
Water:	61.0 %	
Coating VOC content:	11.07 %	
0	291.7 g/l / 2.43 lb/gal	
Material VOC content:	111.9 g/l / 0.93 lb/gal	
Solids content:	26.8 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects

· Acute toxicity:

· LD/LC50	values tha	t are relevant for classification:
111-76-2	2-butoxye	thanol
Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)
		(Contd. on page 8)



acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Trade name: W810 CARBON BLACK

(Contd. of page 7)

3

3

2B

Page 8/11

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

111-76-2 2-butoxyethanol

67-63-0 propan-2-ol

140-88-5 ethyl acrylate

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 9)

Page 9/11

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Trade name: W810 CARBON BLACK

(Contd. of page 8)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number	NOT APPLICABLE	
UN proper shipping name	N/A NOT APPLICABLE	
Transport hazard class(es)	NOT APPLICABLE NOT APPLICABLE	
Packing group	NON APPLICABILE NOT APPLICABLE	
Environmental hazards: Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Anne MARPOL73/78 and the IBC Code	ex II of Not applicable.	

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

111-76-2 2-butoxyethanol

67-63-0 propan-2-ol

140-88-5 ethyl acrylate

(Contd. on page 10)



Page 10/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

Trade name: W810 CARBON BLACK

TSCA /To	xic Substances Control Act):	(Contd. of page
•	water, distilled, conductivity or of similar purity	ACTIV
	2-butoxyethanol	ACTIV
	propan-2-ol	ACTIV
	2-dimethylaminoethanol	ACTIV
	2-Ethyl-1-hexanol	ACTIV
	ethyl acrylate	ACTIV
Hazardou	s Air Pollutants	
140-88-5	ethyl acrylate	
Propositi	on 65	
Chemical	s known to cause cancer:	
140-88-5	ethyl acrylate	
Chemical	s known to cause reproductive toxicity for females:	
None of th	e ingredients is listed.	
- Chemical	s known to cause reproductive toxicity for males:	
None of th	e ingredients is listed.	
· Chemical	s known to cause developmental toxicity:	
None of th	e ingredients is listed.	
Carcinog	enic categories	
· EPA (Env	ironmental Protection Agency)	
111-76-2	2-butoxyethanol	Ν
TLV (Thre	eshold Limit Value)	
111-76-2	2-butoxyethanol	A
67-63-0	propan-2-ol	A
140-88-5	ethyl acrylate	A
NIOSH-Ca	a (National Institute for Occupational Safety and Health)	· · · · · · · · · · · · · · · · · · ·
4 40 00 5	ethyl acrylate	

The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms



· Signal word Warning

- US



Page 11/11

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/08/2025

Hazard statements
 Combustible liquid.

Reviewed on 05/08/2025

Trade name: W810 CARBON BLACK

(Contd. of page 10)

Causes serious eye irritation. • **Precautionary statements** Keep away from flames and hot surfaces. – No smoking. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations. • **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 05/08/2025 / 1.0

· Abbreviations and acronyms: EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, ÉU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable liquids 4: Flammable liquids - Category 4 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A • * Data compared to the previous version altered.

US -