

Page 1/10

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

1 Identification

- · Product identifier
- · Trade name: W850 STANDARD BLACK
- · Article number: W850
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

General Paint Co. SAL

P.O. Box 7623

Beirut

LEBANON

info@hymax.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture

Flammable liquids 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements

Combustible liquid.

· Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 2 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0 Fire = 2

Reactivity = 0



Page 2/10

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W850 STANDARD BLACK

(Contd. of page 1)

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

| · <i>[</i> | Dangerou | is components: | |
|------------|----------|-----------------|--------------------|
| 1 | 111-76-2 | 2-butoxyethanol | >2.5- <i>≤</i> 10% |
| | 67-63-0 | propan-2-ol | >2.5- <i>≤</i> 10% |

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)



Page 3/10

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W850 STANDARD BLACK

(Contd. of page 2)

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

| · PAC-1: | | |
|----------|------------------------|-------------|
| 111-76-2 | 2-butoxyethanol | 60 ppm |
| 67-63-0 | propan-2-ol | 400 ppm |
| 108-01-0 | 2-dimethylaminoethanol | 3.7 ppm |
| 140-88-5 | ethyl acrylate | 8.3 ppm |
| · PAC-2: | | |
| 111-76-2 | 2-butoxyethanol | 120 ppm |
| 67-63-0 | propan-2-ol | 2000* ppm |
| 108-01-0 | 2-dimethylaminoethanol | 12 ppm |
| 140-88-5 | ethyl acrylate | 36 ppm |
| · PAC-3: | | |
| 111-76-2 | 2-butoxyethanol | 700 ppm |
| 67-63-0 | propan-2-ol | 12000** ppm |
| 108-01-0 | 2-dimethylaminoethanol | 72 ppm |
| 140-88-5 | ethyl acrylate | 240 ppm |

7 Handling and storage

- Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class: 10

(Contd. on page 4)



Page 4/10

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W850 STANDARD BLACK

(Contd. of page 3)

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m³, 50 ppm

Skir

REL Long-term value: 24 mg/m³, 5 ppm

Skin

TLV Long-term value: 97 mg/m³, 20 ppm

BEI, A3

67-63-0 propan-2-ol

PEL Long-term value: 980 mg/m³, 400 ppm

REL Short-term value: 1225 mg/m³, 500 ppm

Long-term value: 980 mg/m³, 400 ppm

TLV Short-term value: 984 mg/m³, 400 ppm

Long-term value: 491 mg/m³, 200 ppm

BEI, A4

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

67-63-0 propan-2-ol

BEI 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.

(Contd. on page 5)



Page 5/10

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W850 STANDARD BLACK

(Contd. of page 4)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

| · Information on basic physical and chemical properties · General Information · Appearance: Form: | | |
|--|------------------------------|----------------------------------|
| Color: Odor: Odor: Characteristic Not determined. PH-value at 20 °C (68 °F): Change in condition Melting point/Melting range: Boiling point/Boiling range: 100 °C (212 °F) Flash point: Not applicable. | General Information | chemical properties |
| Odor: Odor threshold: Not determined. PH-value at 20 °C (68 °F): Change in condition Melting point/Melting range: Boiling point/Boiling range: 100 °C (212 °F) Flash point: Not applicable. | Form: | Fluid |
| Odor threshold: Not determined. pH-value at 20 °C (68 °F): 7.4-8.4 Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 100 °C (212 °F) Flash point: 68 °C (154.4 °F) Flammability: Not applicable. | Color: | According to product description |
| pH-value at 20 °C (68 °F): 7.4-8.4 Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 100 °C (212 °F) Flash point: 68 °C (154.4 °F) Flammability: Not applicable. | · Odor: | Characteristic |
| · Change in condition Melting point/Melting range: Boiling point/Boiling range: 100 °C (212 °F) · Flash point: 68 °C (154.4 °F) · Flammability: Not applicable. | · Odor threshold: | Not determined. |
| Melting point/Melting range: Boiling point/Boiling range:Undetermined. 100 °C (212 °F)Flash point:68 °C (154.4 °F)Flammability:Not applicable. | · pH-value at 20 °C (68 °F): | 7.4-8.4 |
| · Flammability: Not applicable. | Melting point/Melting range: | |
| | · Flash point: | 68 °C (154.4 °F) |
| · Auto igniting: 240 °C (464 °F) | · Flammability: | Not applicable. |
| | · Auto igniting: | 240 °C (464 °F) |
| · Decomposition temperature: Not determined. | · Decomposition temperature: | Not determined. |
| · Ignition temperature: Product is not selfigniting. | · Ignition temperature: | Product is not selfigniting. |

(Contd. on page 6)



Page 6/10

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W850 STANDARD BLACK

| | (Contd. of pag |
|--|--|
| · Danger of explosion: | Not determined. |
| · Explosion limits: | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| · Vapor pressure at 20 °C (68 °F): | 23 hPa (17.3 mm Hg) |
| · Density at 20 °C (68 °F): | 1.035 g/cm³ (8.63707 lbs/gal) |
| Relative density | Not determined. |
| · Vapor density | Not determined. |
| Evaporation rate | Not determined. |
| · Solubility in / Miscibility with | |
| Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/wat | e er): Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 9.7 % |
| Water: | 65.8 % |
| Coating VOC content: | 9.73 % |
| - | 315.8 g/l / 2.64 lb/gal |
| Material VOC content: | 100.7 g/l / 0.84 lb/gal |
| Solids content: | 23.4 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

US



Page 7/10

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W850 STANDARD BLACK

(Contd. of page 6)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

111-76-2 2-butoxyethanol

| | z-butoxye | |
|------------|-----------|---|
| Oral | LD50 | 1,200 mg/kg (ATE) |
| | | 1,200 mg/kg (ATE) 1,480 mg/kg (rat) 400 mg/kg (rab) |
| Dermal | LD50 | 400 mg/kg (rab) |
| Inhalative | LC50/4 h | 3 mg/l (ATE) |
| | | |

- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- Carcinogenic categories

| · IARC (Int | · IARC (International Agency for Research on Cancer) | | | |
|-------------|--|----|--|--|
| 111-76-2 | 2-butoxyethanol | 3 | | |
| 67-63-0 | propan-2-ol | 3 | | |
| 140-88-5 | ethyl acrylate | 2B | | |

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 8)



Page 8/10

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W850 STANDARD BLACK

(Contd. of page 7)

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

| UN-Number | NOT APPLICABLE |
|---|-----------------------------------|
| on propor omponing name | N/A NOT APPLICABLE |
| | NOT APPLICABLE NOT APPLICABLE |
| | NON APPLICABILE NOT APPLICABLE |
| Environmental hazards: Marine pollutant: | No |
| Special precautions for user | Not applicable. |

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 9)



Page 9/10

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W850 STANDARD BLACK

| | | (Contd. of page |
|----------------------------------|---|-----------------|
| | 3 (Specific toxic chemical listings): | |
| | -butoxyethanol | |
| 67-63-0 pi | • | |
| 140-88-5 e | thyl acrylate | |
| · TSCA (Tox | ic Substances Control Act): | |
| 7732-18-5 | water, distilled, conductivity or of similar purity | ACTIVE |
| 111-76-2 | 2-butoxyethanol | ACTIVE |
| | propan-2-ol | ACTIVI |
| | 2-dimethylaminoethanol | ACTIVE |
| | Dipropylene glycol (isomer unspecified) | ACTIVI |
| 140-88-5 | ethyl acrylate | ACTIVI |
| · Hazardous | Air Pollutants | |
| 140-88-5 e | thyl acrylate | |
| Proposition | 1 65 | |
| Chemicals known to cause cancer: | | |
| 140-88-5 ethyl acrylate | | |
| · Chemicals | known to cause reproductive toxicity for females: | |
| None of the | ingredients is listed. | |
| · Chemicals | known to cause reproductive toxicity for males: | |
| None of the | ingredients is listed. | |
| · Chemicals | known to cause developmental toxicity: | |
| None of the | ingredients is listed. | |
| · Carcinoger | nic categories | |
| _ | onmental Protection Agency) | |
| • | butoxyethanol | N |
| · TLV (Thres | hold Limit Value) | |
| • | butoxyethanol | A |
| 67-63-0 p | • | A |
| 140-88-5 e | thyl acrylate | A |
| · NIOSH-Ca | (National Institute for Occupational Safety and Health) | <u> </u> |
| 140-88-5 e | | |
| · GHS label e | | |

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms Void
- · Signal word Warning

(Contd. on page 10)



Page 10/10

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W850 STANDARD BLACK

(Contd. of page 9)

· Hazard statements

Combustible liquid.

· Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 05/08/2025 / 1.0
- · Abbreviations and acronyms:

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable liquids 4: Flammable liquids - Category 4

* Data compared to the previous version altered.