

Page 1/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025

Reviewed on 05/08/2025

1 Identification

- · Product identifier
- · Trade name: W860 GRAYISH BLACK
- · Article number: W860
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

General Paint Co. SAL

P.O. Box 7623

Beirut

LEBANON

info@hymax.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A H

H319 Causes serious eye irritation.

Flammable liquids 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard statements

Combustible liquid.

Causes skin irritation.

Causes serious eye irritation.

· Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

(Contd. on page 2)



Page 2/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W860 GRAYISH BLACK

(Contd. of page 1)

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water. Specific treatment (see on this label).

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 2 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 2 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
111-76-2	2-butoxyethanol	>10- <i>≤</i> 25%	
67-63-0	propan-2-ol	<i>≤</i> 2.5%	

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)



acc. to OSHA HCS

Page 3/11

Printing date 05/08/2025

Reviewed on 05/08/2025

Trade name: W860 GRAYISH BLACK

(Contd. of page 2)

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:		
111-76-2	2-butoxyethanol	60 ppm
67-63-0	propan-2-ol	400 ppm
108-01-0	2-dimethylaminoethanol	3.7 ppm
140-88-5	ethyl acrylate	8.3 ppm
PAC-2:		
111-76-2	2-butoxyethanol	120 ppm
		Contd. on page 4

US





Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W860 GRAYISH BLACK

67-63-0	propan-2-ol	(Contd. of page 3) 2000* ppm
108-01-0	2-dimethylaminoethanol	12 ppm
140-88-5	ethyl acrylate	36 ppm
PAC-3:		
111-76-2	2-butoxyethanol	700 ppm
67-63-0	propan-2-ol	12000** ppm
108-01-0	2-dimethylaminoethanol	72 ppm
140-88-5	ethyl acrylate	240 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m³, 50 ppm

Skin

REL Long-term value: 24 mg/m³, 5 ppm

Skii

TLV Long-term value: 97 mg/m³, 20 ppm

BEI, A3

67-63-0 propan-2-ol

PEL Long-term value: 980 mg/m³, 400 ppm

(Contd. on page 5)



Page 5/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W860 GRAYISH BLACK

(Contd. of page 4)

REL Short-term value: 1225 mg/m³, 500 ppm

Long-term value: 980 mg/m³, 400 ppm TLV Short-term value: 984 mg/m³, 400 ppm Long-term value: 491 mg/m³, 200 ppm

BEI, A4

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

67-63-0 propan-2-ol

BEI 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)



Page 6/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W860 GRAYISH BLACK

(Contd. of page 5)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

· Evaporation rate



Tightly sealed goggles

Physical and chemical prope	erties			
Information on basic physical and chemical properties				
General Information				
· Appearance:				
Form:	Fluid			
Color:	According to product description			
· Odor:	Characteristic			
· Odor threshold:	Not determined.			
· pH-value at 20 °C (68 °F):	7.4-8.4			
· Change in condition				
Melting point/Melting range:	Undetermined.			
Boiling point/Boiling range:	100 °C (212 °F)			
· Flash point:	68 °C (154.4 °F)			
· Flammability:	Not applicable.			
· Auto igniting:	240 °C (464 °F)			
Decomposition temperature:	Not determined.			
· Ignition temperature:	Product is not selfigniting.			
Danger of explosion:	Not determined.			
· Explosion limits:				
Lower:	1.1 Vol %			
Upper:	10.6 Vol %			
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)			
· Density at 20 °C (68 °F):	1.027 g/cm³ (8.57032 lbs/gal)			
· Relative density `	Not determined.			
· Vapor density	Not determined.			

Not determined.

(Contd. on page 7)





Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W860 GRAYISH BLACK

		(Contd. of page
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/	water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	11.7 %	
Water:	63.1 %	
Coating VOC content:	11.66 %	
J	340.4 g/l / 2.84 lb/gal	
Material VOC content:	119.8 g/l / 1.00 lb/gal	
Solids content:	24.1 %	
· Other information	No further relevant information available	le.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	values	that are	relevant t	for ci	lassificat	tion:
LD/LOO	values	triat arc	ICICVAILL	Oi Ci	assiiicai	vii.

111-76-2 2-butoxyethanol Oral LD50 1,200 mg/kg (ATE) 1,480 mg/kg (rat) 1,480 mg/kg (rat) Dermal LD50 400 mg/kg (rab) Inhalative LC50/4 h 3 mg/l (ATE)

(Contd. on page 8)



Page 8/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W860 GRAYISH BLACK

(Contd. of page 7)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

•	· ·		
· IARC (Int	ernational Agency for Research on Cancer)		
111-76-2	2-butoxyethanol	3	
67-63-0	propan-2-ol	3	
140-88-5	ethyl acrylate	2B	
· NTP (Nat	ional Toxicology Program)		
None of the	None of the ingredients is listed.		
· OSHA-Ca	· OSHA-Ca (Occupational Safety & Health Administration)		
None of the	ne ingredients is listed.		

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

US



Page 9/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W860 GRAYISH BLACK

(Contd. of page 8)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information		
· UN-Number	NOT APPLICABLE	
· UN proper shipping name	N/A NOT APPLICABLE	
· Transport hazard class(es)	NOT APPLICABLE NOT APPLICABLE	
· Packing group	NON APPLICABILE NOT APPLICABLE	
· Environmental hazards: · Marine pollutant:	No	
· Special precautions for user	Not applicable.	
· Transport in bulk according to Annex MARPOL73/78 and the IBC Code	x II of Not applicable.	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

111-76-2 2-butoxyethanol

67-63-0 propan-2-ol

140-88-5 ethyl acrylate

(Contd. on page 10)



Page 10/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2025 Reviewed on 05/08/2025

Trade name: W860 GRAYISH BLACK

		(Contd. of page
TSCA (To	ric Substances Control Act):	
7732-18-5	water, distilled, conductivity or of similar purity	ACTIV
111-76-2	2-butoxyethanol	ACTIV
67-63-0	propan-2-ol	ACTIV
108-01-0	2-dimethylaminoethanol	ACTIV
140-88-5	ethyl acrylate	ACTIV
Hazardou	s Air Pollutants	•
140-88-5	ethyl acrylate	
Proposition	n 65	
Chemicals	known to cause cancer:	
140-88-5	ethyl acrylate	
Chemicals	known to cause reproductive toxicity for females:	
None of the	e ingredients is listed.	
Chemicals	known to cause reproductive toxicity for males:	
None of the	e ingredients is listed.	
Chemicals	known to cause developmental toxicity:	
None of the	e ingredients is listed.	

· Carcinogenic categories

· EPA (Env	ironmental Protection Agency)		
111-76-2	2-butoxyethanol	NL	
· TLV (Thre	eshold Limit Value)		
111-76-2	2-butoxyethanol	A3	
	propan-2-ol	A4	
140-88-5	ethyl acrylate	A4	
· NIOSH-C	· NIOSH-Ca (National Institute for Occupational Safety and Health)		

140-88-5 ethyl acrylate

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Warning

(Contd. on page 11)



Page 11/11

Safety Data Sheet acc. to OSHA HCS

Reviewed on 05/08/2025 Printing date 05/08/2025

Trade name: W860 GRAYISH BLACK

(Contd. of page 10)

· Hazard statements

Combustible liquid.

Causes skin irritation.

Causes serious eye irritation.

· Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water. Specific treatment (see on this label).

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 05/08/2025 / 1.0
- · Abbreviations and acronyms:

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable liquids 4: Flammable liquids – Category 4 Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

* Data compared to the previous version altered.