

Page 1/15

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 08/28/2024

# 1 Identification

· Product identifier

- · Trade name: B300 BASECOAT VIOLA FANTASY
- · Article number: B300
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

• *Manufacturer/Supplier:* General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@hymax.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

### 2 Hazard(s) identification

· Classification of the substance or mixture GHS02 Flame Flammable Liquids 3 H226 Flammable liquid and vapor. GHS08 Health hazard Carcinogenicity 2 H351 Suspected of causing cancer. Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to the hearing organs 2 through prolonged or repeated exposure. GHS07 Skin Irritation 2 H315 Causes skin irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2) US



# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 08/28/2024

Page 2/15

#### Trade name: B300 BASECOAT VIOLA FANTASY

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 Signal word Warning · Hazard-determining components of labeling: n-butyl acetate ethylbenzene · Hazard statements Flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eve protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 3)

US



# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 08/28/2024

Page 3/15

#### Trade name: B300 BASECOAT VIOLA FANTASY

(Contd. of page 2) · Classification system: NFPA ratings (scale 0 - 4) Health = 1Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 1 Health = 1FIRE 3 Fire = 3Reactivity = 0**REACTIVITY** 0 · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

# 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

<ul> <li>Dangerous</li> </ul>	components:
-------------------------------	-------------

Dangereue		
123-86-4	n-butyl acetate	>50- <i>≤</i> 100%
1330-20-7	xylene	>10- <i>≤</i> 25%
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%
108-65-6	2-methoxy-1-methylethyl acetate	<i>≤</i> 2.5%
100-41-4	ethylbenzene	<i>≤</i> 2.5%

#### 4 First-aid measures

#### · Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation: In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 08/28/2024

### Trade name: B300 BASECOAT VIOLA FANTASY

- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

· PAC-1:		
	n-butyl acetate	5 ppm
1330-20-7		130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
	ethylbenzene	33 ppm
	1-methoxy-2-propanol	100 ppm
7664-38-2	phosphoric acid	3 mg/m <sup>3</sup>
70657-70-4	2-methoxypropyl acetate	50 ppm
	A	(Contd. on page 5)

(Contd. of page 3)

Page 4/15

Page 5/15

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 08/28/2024

### Trade name: B300 BASECOAT VIOLA FANTASY

		(Contd. of page 4)
· PAC-2:		
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
100-41-4	ethylbenzene	1100* ppm
107-98-2	1-methoxy-2-propanol	160 ppm
7664-38-2	phosphoric acid	30 mg/m <sup>3</sup>
70657-70-4	2-methoxypropyl acetate	1,000 ppm
· PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
100-41-4	ethylbenzene	1800* ppm
107-98-2	1-methoxy-2-propanol	660 ppm
7664-38-2	phosphoric acid	150 mg/m <sup>3</sup>
	2-methoxypropyl acetate	5,000 ppm

# 7 Handling and storage

#### · Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
   Open and handle receptacle with care.
   Prevent formation of aerosols.
   Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- Specific end use(s) No further relevant information available.

(Contd. on page 6)

us

Г

Page 6/15

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 08/28/2024

# Trade name: B300 BASECOAT VIOLA FANTASY

(Contd. of page 5)

US

	osure controls/personal protection				
· <b>Com</b> The f recor	rol parameters conents with limit values that require monitoring at the workplace: ollowing constituents are the only constituents of the product which have a PEL, TLV or othe nmended exposure limit. s time, the remaining constituent has no known exposure limits.				
	123-86-4 n-butyl acetate				
PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm				
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm				
TLV	Short-term value: 150 ppm Long-term value: 50 ppm				
1330	20-7 xylene				
PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm				
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm				
TLV	Long-term value: 20 ppm BEI, A4				
108-6	5-6 2-methoxy-1-methylethyl acetate				
WEE	L Long-term value: 50 ppm				
100-41-4 ethylbenzene					
PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm				
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm				
TLV	Long-term value: 20 ppm OTO, BEI, A3				
-	dients with biological limit values:				
1330	20-7 xylene				
1	1.5 g/g creatinine Medium: urine Fime: end of shift Parameter: Methylhippuric acids				
100-4	1-4 ethylbenzene				
1	).15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)				
	(Contd. on page 3				



Page 7/15

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 08/28/2024

### Trade name: B300 BASECOAT VIOLA FANTASY

(Contd. of page 6) · Additional information: The lists that were valid during the creation were used as basis. · Exposure controls · Personal protective equipment: · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin. · Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the dearadation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 8)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 08/28/2024

# Trade name: B300 BASECOAT VIOLA FANTASY

(Contd. of page 7)

Page 8/15

· Information on basic physical and (	chemical properties
· General Information	
· Appearance:	
Form:	Liquid
Color:	Violet
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124 °C (255.2 °F)
· Flash point:	27 °C (80.6 °F)
· Flammability:	Flammable.
· Auto igniting:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive ai vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
· Density at 20 °C (68 °F):	0.965 g/cm³ (8.05293 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
· Viscosity:	·
Dynamic:	Not determined.
Kinematic:	Not determined.

#### Page 9/15

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 08/28/2024

### Trade name: B300 BASECOAT VIOLA FANTASY

	(Contd. of page 8)
74.7 %	
74.67 %	
720.5 g/l / 6.01 lb/gal	
720.5 g/l / 6.01 lb/gal	
25.3 %	
No further relevant information available.	
	74.67 % 720.5 g/l / 6.01 lb/gal 720.5 g/l / 6.01 lb/gal 25.3 %

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

#### 123-86-4 n-butyl acetate

	-	
	LD50	13,100 mg/kg (rat)
Dermal	LD50	13,100 mg/kg (rat) >5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

### · Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 10)

US -

Page 10/15

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 08/28/2024

### Trade name: B300 BASECOAT VIOLA FANTASY

(Contd. of page 9)

3

2B

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7 xylene

100-41-4 ethylbenzene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

# 12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 11)

US

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 08/28/2024

# Trade name: B300 BASECOAT VIOLA FANTASY

(Contd. of page 10)

Page 11/15

UN-Number		
DOT, ADR, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint	
ADR	1263 PAINT	
IMDG, IATA	PAINT	
Transport hazard class(es)	NOT APPLICABLE	
DOT		
Class Label	3 Flammable liquids 3	
ADR, IMDG		
Class	3 Flammable liquids	
Label	3	
Class	8 Corrosive substances	
Label	3	
Packing group		
DOT, ADR, IATA	///	
IMDG	Void	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user EMS Number:	Warning: Flammable liquids F-E,S-E	



Page 12/15

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 08/28/2024

# Trade name: B300 BASECOAT VIOLA FANTASY

	(Contd. of page 2
· Stowage Category	A
<ul> <li>Transport in bulk according to Annex MARPOL73/78 and the IBC Code</li> </ul>	Il of Not applicable.
· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
• ADR • Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

# 15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. · Sara

	55 (extremely hazardous substances):	
None of the	e ingredients is listed.	
Section 31	13 (Specific toxic chemical listings):	
1330-20-7	xylene	
100-41-4	ethylbenzene	
7664-38-2	phosphoric acid	
TSCA (To	xic Substances Control Act):	
123-86-4	n-butyl acetate	ACTIVE
1330-20-7	xylene	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
100-41-4	ethylbenzene	ACTIVE
107 00 0	1-methoxy-2-propanol	ACTIVE
107-96-2		
	phosphoric acid	ACTIVE

Page 13/15

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 08/28/2024

# Trade name: B300 BASECOAT VIOLA FANTASY

1330-20-7	s Air Pollutants	
	ethylbenzene	
Propositio		
•	s known to cause cancer:	
	ethylbenzene	
	s known to cause reproductive toxicity for females:	
	e ingredients is listed.	
	s known to cause reproductive toxicity for males:	
	e ingredients is listed.	
	s known to cause developmental toxicity:	
None of th	e ingredients is listed.	
Carcinoge	enic categories	
-	ironmental Protection Agency)	
1330-20-7		
100-41-4	ethylbenzene	
TLV (Thre	shold Limit Value)	
1330-20-7	xylene	F
100-41-4	ethylbenzene	A
NIOSH-Ca	(National Institute for Occupational Safety and Health)	
None of th	e ingredients is listed.	
Hazard pi	ct is classified and labeled according to the Globally Harmonized System (GHS).	
0	rd Warning	

- n-butyl acetate ethylbenzene
- · Hazard statements Flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer.



Page 14/15

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 08/28/2024

# Trade name: B300 BASECOAT VIOLA FANTASY

(Contd. of page 13) May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 01/10/2025 / 1.1
- Abbreviations and acronyms: ICAO: International Civil Aviation Organisation RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transport Association IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 15)

ÚS



# Safety Data Sheet acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 08/28/2024

Page 15/15

# Trade name: B300 BASECOAT VIOLA FANTASY

	Contd. of page 14)
ELINCS: European List of Notified Chemical Substances	10,
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, ÉU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flammable Liquids 3: Flammable liquids – Category 3	
Skin Irritation 2: Skin corrosion/irritation – Category 2	
Carcinogenicity 2: Carcinogenicity – Category 2	
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3	2
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Cate	
$\cdot$ * Data compared to the previous version altered.	.90.7 =
	US