

Page 1/15

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

1 Identification

· Product identifier

- · Trade name: <u>B740 BASECOAT PEARL VIOLET</u>
- · Article number: B740
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

• *Manufacturer/Supplier:* General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@hymax.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

Classification of the substance or mixture GHS02 Flame Flammable Liquids 3 H226 Flammable liquid and vapor. Flammable Liquids 3 H226 Flammable liquid and vapor. GHS08 Health hazard Germ Cell Mutagenicity 1B H340 May cause genetic defects. Carcinogenicity 1B H350 May cause cancer. GHS07 Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)



acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Page 2/15

Trade name: B740 BASECOAT PEARL VIOLET

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 Signal word Danger · Hazard-determining components of labeling: n-butyl acetate Naphtha (petroleum), hydrotreated heavy ethvlbenzene · Hazard statements Flammable liquid and vapor. May cause genetic defects. May cause cancer. May cause drowsiness or dizziness. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 0Fire = 3Reactivity = 0

(Contd. on page 3)

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B740 BASECOAT PEARL VIOLET

· HMIS-ratings (scale 0 - 4)

HEALTH*0Health = *0FIRE3Fire = 3REACTIVITY0Reactivity = 0

· Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
123-86-4	n-butyl acetate	>50- <i>≤</i> 100%
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%
1330-20-7	xylene	>2.5- <i>≤</i> 10%
64742-48-9	Naphtha (petroleum), hydrotreated heavy	>2.5- <i>≤</i> 10%
100-41-4	ethylbenzene	<i>≤</i> 2.5%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

- US

(Contd. on page 4)

(Contd. of page 2)

Page 3/15

Page 4/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B740 BASECOAT PEARL VIOLET

(Contd. of page 3)

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m ³
100-41-4	ethylbenzene	33 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
7664-38-2	phosphoric acid	3 mg/m ³
70657-70-4	2-methoxypropyl acetate	50 ppm
PAC-2:		
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m ³
100-41-4	ethylbenzene	1100* ppm
107-98-2	1-methoxy-2-propanol	160 ppm

Page 5/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B740 BASECOAT PEARL VIOLET

108-65-6	2-methoxy-1-methylethyl acetate	(Contd. of page 4) 1,000 ppm
7664-38-2	phosphoric acid	30 mg/m ³
70657-70-4	2-methoxypropyl acetate	1,000 ppm
· PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
100-41-4	ethylbenzene	1800* ppm
107-98-2	1-methoxy-2-propanol	660 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
7664-38-2	phosphoric acid	150 mg/m³
70657-70-4	2-methoxypropyl acetate	5,000 ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

 Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 6)



acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Page 6/15

Trade name: B740 BASECOAT PEARL VIOLET (Contd. of page 5) · Control parameters Components with limit values that require monitoring at the workplace: The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits. 123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV Short-term value: 150 ppm Long-term value: 50 ppm 1330-20-7 xylene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 20 ppm BEI, A4 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 20 ppm OTO, BEI, A3 · Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 q/q creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids 100-41-4 ethylbenzene BEI 0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific) · Additional information: The lists that were valid during the creation were used as basis. · Exposure controls · Personal protective equipment: · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. (Contd. on page 7)

- US



Page 7/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

· pH-value:

Reviewed on 01/10/2025

Trade name: B740 BASECOAT PEARL VIOLET

(Contd. of page 6) Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. · Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. · Eye protection: Tightly sealed goggles 9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Liquid Color: Violet · Odor: Characteristic · Odor threshold: Not determined.

Not determined.

(Contd. on page 8)

US

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B740 BASECOAT PEARL VIOLET

	(Contd. of page
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 124 °C (255.2 °F)
Flash point:	27 °C (80.6 °F)
Flammability:	Flammable.
Auto igniting:	370 °C (698 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive ai vapor mixtures are possible.
Explosion limits: Lower: Upper:	1.2 Vol % 7.5 Vol %
Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate	0.984 g/cm ³ (8.21148 lbs/gal) Not determined. Not determined. Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
Solvent content: Organic solvents: Coating VOC content:	74.6 % 74.58 % 733.9 g/l / 6.12 lb/gal
Material VOC content:	733.9 g/l / 6.12 lb/gal
Solids content:	27.2 %
Other information	No further relevant information available.

(Contd. on page 9)

Page 8/15

Page 9/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B740 BASECOAT PEARL VIOLET

(Contd. of page 8)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant	for classification:
------------------------------------	---------------------

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

Primary irritant effect:

- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7 xylene

100-41-4 ethylbenzene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 10)

3

2B

119

Page 10/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B740 BASECOAT PEARL VIOLET

(Contd. of page 9)

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, ADR, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint	
ADR	1263 PAINT	
IMDG, IATA	PAINT	



Page 11/15

Safety Data Sheet acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B740 BASECOAT PEARL VIOLET

	(Contd. of pa	age 1
Transport hazard class(es)	NOT APPLICABLE	
DOT		
P MAILET FLOR		
Class	3 Flammable liquids	
Label	3	
ADR, IMDG		
Class	3 Flammable liquids	
Label	3	
ΙΑΤΑ		
Class	8 Corrosive substances	
Label	8	
Packing group DOT	11	
ADR, IMDG, IATA	// ///	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	
EMS Number:	F-E,S-E	
Stowage Category	A	
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.	
Transport/Additional information:		
DOT		
Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L	
	(Contd. on pa	aae 1

Page 12/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B740 BASECOAT PEARL VIOLET

	(Contd. of page 1
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

None of the	e ingredients is listed.	
Section 31	3 (Specific toxic chemical listings):	
1330-20-7	xylene	
100-41-4	ethylbenzene	
7664-38-2	phosphoric acid	
TSCA (Tox	ic Substances Control Act):	
123-86-4	n-butyl acetate	ACTIVE
1330-20-7	xylene	ACTIVE
64742-48-9	Naphtha (petroleum), hydrotreated heavy	ACTIVE
100-41-4	ethylbenzene	ACTIVE
107-98-2	1-methoxy-2-propanol	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
7664-38-2	phosphoric acid	ACTIV
Hazardous	Air Pollutants	
1330-20-7	xylene	
100-41-4	ethylbenzene	
Propositio	n 65	
Chemicals	known to cause cancer:	
100 11 1	thylbenzene	



Page 13/15

(Contd. of page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B740 BASECOAT PEARL VIOLET

· Chemical	s known to cause reproductive toxicity for females:	(Contd. of page 12
	e ingredients is listed.	
· Chemical	s known to cause reproductive toxicity for males:	
None of th	e ingredients is listed.	
· Chemical	s known to cause developmental toxicity:	
None of th	e ingredients is listed.	
· Carcinog	enic categories	
· EPA (Env	ironmental Protection Agency)	
1330-20-7	xylene	1
100-41-4	ethylbenzene	D
· TLV (Thre	eshold Limit Value)	
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
NIOSH-Ca	a (National Institute for Occupational Safety and Health)	

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

n-butyl acetate Naphtha (petroleum), hydrotreated heavy ethylbenzene

Hazard statements
 Flammable liquid and vapor.
 May cause genetic defects.
 May cause cancer.
 May cause drowsiness or dizziness.

Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment.

(Contd. on page 14)

US



Page 14/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B740 BASECOAT PEARL VIOLET

(Contd. of page 13) Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · National regulations:

 Information about limitation of use: Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 01/10/2025 / 1.0
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 15)

US



acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B740 BASECOAT PEARL VIOLET

(Contd. of page 14)

US

Page 15/15

NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B Carcinogenicity 1B: Carcinogenicity – Category 1B Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 • * **Data compared to the previous version altered.**