

Page 1/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

1 Identification

· Product identifier

- · Trade name: B775 BASECOAT GREEN-ROSE EXTREME
- · Article number: B775
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

• *Manufacturer/Supplier:* General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@hymax.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture GHS02 Flame Flammable Liquids 3 H226 Flammable liquid and vapor. GHS08 Health hazard Carcinogenicity 2 H351 Suspected of causing cancer. Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to the hearing organs through prolonged or repeated exposure. 2 GHS07 Skin Irritation 2 H315 Causes skin irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2) US



Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Page 2/15

Trade name: B775 BASECOAT GREEN-ROSE EXTREME

(Contd. of page 1) Hazard pictograms GHS02 GHS07 GHS08 Signal word Warning · Hazard-determining components of labeling: n-butyl acetate ethylbenzene · Hazard statements Flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eve protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 3)

- US -



Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Page 3/15

Trade name: B775 BASECOAT GREEN-ROSE EXTREME

(Contd. of page 2) · Classification system: NFPA ratings (scale 0 - 4) Health = 1Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 1 Health = 1FIRE Fire = 33 Reactivity = 0**REACTIVITY** 0 · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

 Dangerous 	components:
-------------------------------	-------------

Dangereue		
123-86-4	n-butyl acetate	>50- <i>≤</i> 100%
1330-20-7	xylene	>10- <i>≤</i> 25%
64742-95-6 Solvent naphtha (petroleum), light arom.		>2.5- <i>≤</i> 10%
108-65-6	2-methoxy-1-methylethyl acetate	<i>≤</i> 2.5%
100-41-4	ethylbenzene	<i>≤</i> 2.5%
	· · · · · · · · · · · · · · · · · · ·	

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation: In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)

US

Page 4/15

(Contd. of page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B775 BASECOAT GREEN-ROSE EXTREME

· Information for doctor:

• Most important symptoms and effects, both acute and delayed No further relevant information available.

• Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.

• Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
	ethylbenzene	33 ppm
	1-methoxy-2-propanol	100 ppm
7664-38-2	phosphoric acid	3 mg/m ³
70657-70-4	2-methoxypropyl acetate	50 ppm
	·	(Contd. on page 5)

Page 5/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B775 BASECOAT GREEN-ROSE EXTREME

		(Contd. of page
PAC-2:		
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppn
100-41-4	ethylbenzene	1100* ppn
107-98-2	1-methoxy-2-propanol	160 ppm
7664-38-2	phosphoric acid	30 mg/m ³
70657-70-4	2-methoxypropyl acetate	1,000 ppn
PAC-3:		
123-86-4	n-butyl acetate	3000* ppn
1330-20-7	xylene	2500* ppr
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppn
100-41-4	ethylbenzene	1800* ppn
107-98-2	1-methoxy-2-propanol	660 ppm
7664-38-2	phosphoric acid	150 mg/m
70657-70-4	2-methoxypropyl acetate	5,000 ppn

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

(Contd. on page 6)

us

Page 6/15

Safety Data Sheet acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B775 BASECOAT GREEN-ROSE EXTREME

(Contd. of page 5)

Addit	ional information about design of technical systems: No further data; see section 7.
Contr	rol parameters
Сотр	ponents with limit values that require monitoring at the workplace:
	ollowing constituents are the only constituents of the product which have a PEL, TLV or othe
	nmended exposure limit. s time, the remaining constituent has no known exposure limits.
	6-4 n-butyl acetate
PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm
	Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 150 ppm
	Long-term value: 50 ppm
	20-7 xylene
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm
	Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4
108-6	5-6 2-methoxy-1-methylethyl acetate
	L Long-term value: 50 ppm
100-4	1-4 ethylbenzene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm
	Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3
Ingre	dients with biological limit values:
1330-	20-7 xylene
	1.5 g/g creatinine
	Aedium: urine
	Time: end of shift Parameter: Methylhippuric acids
	1-4 ethylbenzene
	0.15 g/g creatinine
۸	Aedium: urine
	Fime: end of shift at end of workweek

Page 7/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B775 BASECOAT GREEN-ROSE EXTREME

(Contd. of page 6) • Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls
- · Personal protective equipment:

 General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 8)

Page 8/15

Safety Data Sheet acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B775 BASECOAT GREEN-ROSE EXTREME

(Contd. of page 7)

 Information on basic physical and General Information 	chemical properties
 Appearance: Form: Color: Odor: Odor threshold: 	Fluid According to product description Characteristic Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 124 °C (255.2 °F)
· Flash point:	27 °C (80.6 °F)
· Flammability:	Flammable.
· Auto igniting:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive an vapor mixtures are possible.
· Explosion limits: Lower: Upper:	1.1 Vol % 7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
 Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate 	0.965 g/cm³ (8.05293 lbs/gal) Not determined. Not determined. Not determined.
 Solubility in / Miscibility with Water: 	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	er): Not determined.
 Viscosity: Dynamic: Kinematic: 	Not determined. Not determined.

Page 9/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B775 BASECOAT GREEN-ROSE EXTREME

	(Contd. of page 8)
73.1 %	
73.11 %	
705.5 g/l / 5.89 lb/gal	
705.5 g/l / 5.89 lb/gal	
26.9 %	
No further relevant information available.	
	73.11 % 705.5 g/l / 5.89 lb/gal 705.5 g/l / 5.89 lb/gal 26.9 %

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	13,100 mg/kg (rat) >5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

· Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 10)

US -

Page 10/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B775 BASECOAT GREEN-ROSE EXTREME

(Contd. of page 9)

3

2B

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7 xylene

100-41-4 ethylbenzene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 11)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B775 BASECOAT GREEN-ROSE EXTREME

(Contd. of page 10)

UN-Number		
DOT, ADR, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint	
ADR	1263 PAINT	
IMDG, IATA	PAINT	
Transport hazard class(es)	NOT APPLICABLE	
DOT		
Class	3 Flammable liquids	
Label	3	
Class Label	3 Flammable liquids 3	
Packing group DOT, ADR, IMDG, IATA		
Environmental hazards: Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	
EMS Number:	F-E,S-E	
Stowage Category	A	
<i>Transport in bulk according to Annex MARPOL73/78 and the IBC Code</i>	ll of Not applicable.	
Transport/Additional information:		
DOT		
Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L	



Page 11/15

Page 12/15

Safety Data Sheet acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B775 BASECOAT GREEN-ROSE EXTREME

	(Contd. of page
ADR	
 Excepted quantities (EQ) 	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· IMDG	
 Limited quantities (LQ) 	5L
· Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. · Sara

	5 (extremely hazardous substances):		
None of the	e ingredients is listed.		
· Section 31	3 (Specific toxic chemical listings):		
1330-20-7	xylene		
100-41-4	ethylbenzene		
7664-38-2	phosphoric acid		
· TSCA (To)	cic Substances Control Act):		
123-86-4	n-butyl acetate	ACTIVE	
1330-20-7	xylene	ACTIVE	
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE	
100-41-4	ethylbenzene	ACTIVE	
107-98-2	1-methoxy-2-propanol	ACTIVE	
7664-38-2	phosphoric acid	ACTIVE	
·Hazardous	s Air Pollutants		
1330-20-7	xylene		
100-41-4	100-41-4 ethylbenzene		
· Propositio	Proposition 65		
· Chemicals	s known to cause cancer:		
100-41-4 е	ethylbenzene		
		(Contd. on page 13	

Page 13/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B775 BASECOAT GREEN-ROSE EXTREME

	(Contd. of page 12)
s known to cause reproductive toxicity for females:	
e ingredients is listed.	
s known to cause reproductive toxicity for males:	
e ingredients is listed.	
s known to cause developmental toxicity:	
e ingredients is listed.	
enic categories	
ironmental Protection Agency)	
xylene	1
ethylbenzene	D
shold Limit Value)	
xylene	A4
ethylbenzene	A3
	e ingredients is listed. s known to cause reproductive toxicity for males: e ingredients is listed. s known to cause developmental toxicity: e ingredients is listed. enic categories ironmental Protection Agency) xylene ethylbenzene shold Limit Value) xylene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



· Signal word Warning

Hazard-determining components of labeling: n-butyl acetate ethylbenzene Hazard statements Flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment.

(Contd. on page 14)

⁻ US

Page 14/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B775 BASECOAT GREEN-ROSE EXTREME

(Contd. of page 13) Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- Contact: N/A
- · Date of preparation / last revision 01/10/2025 / 1.0
- · Abbreviations and acronvms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 15)

[·]US

Page 15/15

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B775 BASECOAT GREEN-ROSE EXTREME

(Contd. of page 14) NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Skin Irritation 2: Skin corrosion/irritation – Category 2 Carcinogenicity 2: Carcinogenicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2 • * Data compared to the previous version altered.