

Page 1/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

1 Identification

· Product identifier

- · Trade name: B988 BASECOAT SILVER DOLLAR FINE
- · Article number: B988
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

• *Manufacturer/Supplier:* General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@hymax.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture GHS02 Flame Flammable Liquids 3 H226 Flammable liquid and vapor. GHS08 Health hazard Carcinogenicity 2 H351 Suspected of causing cancer. Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to the hearing organs 2 through prolonged or repeated exposure. GHS07 Skin Irritation 2 H315 Causes skin irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2) US



Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Page 2/15

Trade name: B988 BASECOAT SILVER DOLLAR FINE

(Contd. of page 1) Hazard pictograms GHS02 GHS07 GHS08 Signal word Warning · Hazard-determining components of labeling: n-butyl acetate ethylbenzene · Hazard statements Flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eve protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 3)

— US

Page 3/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B988 BASECOAT SILVER DOLLAR FINE

(Contd. of page 2) · Classification system: NFPA ratings (scale 0 - 4) Health = 1Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 1 Health = 1 FIRE 3 Fire = 3Reactivity = 0**REACTIVITY** 0 · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

•	Dang	erous	compo	onents:
---	------	-------	-------	---------

2		
123-86-4	n-butyl acetate	>25- <i>≤</i> 50%
1330-20-7	xylene	>10- <i>≤</i> 25%
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%
7429-90-5	aluminium powder (stabilised)	>2.5- <i>≤</i> 10%
100-41-4	ethylbenzene	>2.5- <i>≤</i> 10%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation: In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)

US

Page 4/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B988 BASECOAT SILVER DOLLAR FINE

· Information for doctor:

(Contd. of page 3)

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away. • Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- · Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

· PAC-1:		
	n-butyl acetate	5 ppm
1330-20-7	•	130 ppm
	ethylbenzene	33 ppm
	butan-1-ol	60 ppm
	1-methoxy-2-propanol	100 ppm
95-63-6	1,2,4-trimethylbenzene	140 ppm
108-67-8	mesitylene	140 ppm
	(Cc	ontd. on page 5)

Page 5/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B988 BASECOAT SILVER DOLLAR FINE

108-65-6	2-methoxy-1-methylethyl acetate	(Contd. of page 50 ppm
	phosphoric acid	3 mg/m ³
70657-70-4	2-methoxypropyl acetate	50 ppm
PAC-2:		
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
71-36-3	butan-1-ol	800 ppm
107-98-2	1-methoxy-2-propanol	160 ppm
95-63-6	1,2,4-trimethylbenzene	360 ppm
108-67-8	mesitylene	360 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
7664-38-2	phosphoric acid	30 mg/m ³
70657-70-4	2-methoxypropyl acetate	1,000 ppm
PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
71-36-3	butan-1-ol	8000** ppm
107-98-2	1-methoxy-2-propanol	660 ppm
95-63-6	1,2,4-trimethylbenzene	480 ppm
108-67-8	mesitylene	480 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
7664-38-2	phosphoric acid	150 mg/m ³
70657-70-4	2-methoxypropyl acetate	5,000 ppm

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
 Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 6)

US

Page 6/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B988 BASECOAT SILVER DOLLAR FINE

(Contd. of page 5)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- **Components with limit values that require monitoring at the workplace:** The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

123-80	δ-4 n-butyl acetate	
PEL L	.ong-term value: 710 mg/m³, 150 ppm	
	Short-term value: 950 mg/m³, 200 ppm .ong-term value: 710 mg/m³, 150 ppm	
	Short-term value: 150 ppm .ong-term value: 50 ppm	
1330-2	20-7 xylene	
PEL L	.ong-term value: 435 mg/m³, 100 ppm	
	Short-term value: 655 mg/m³, 150 ppm .ong-term value: 435 mg/m³, 100 ppm	
	ong-term value: 20 ppm BEI, A4	
100-4	-4 ethylbenzene	
PEL L	.ong-term value: 435 mg/m³, 100 ppm	
	Short-term value: 545 mg/m³, 125 ppm .ong-term value: 435 mg/m³, 100 ppm	
	ong-term value: 20 ppm DTO, BEI, A3	
· Ingred	lients with biological limit values:	
1330-2	20-7 xylene	
	5 g/g creatinine ledium: urine	
T	ime: end of shift	
P	arameter: Methylhippuric acids	
		(Contd. on page



Page 7/15

(Contd. of page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B988 BASECOAT SILVER DOLLAR FINE

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine Medium: urine

Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)

US

Page 8/15

(Contd. of page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B988 BASECOAT SILVER DOLLAR FINE

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

General Information	
Appearance: Form:	Liquid
Color:	Silver grey
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124 °C (255.2 °F)
Flash point:	24 °C (75.2 °F)
Flammability:	Flammable.
Auto igniting:	370 °C (698 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
Density at 20 °C (68 °F):	0.951 g/cm³ (7.9361 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

Page 9/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B988 BASECOAT SILVER DOLLAR FINE

	(Contd. of pa	age
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/	water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	75.5 %	
Coating VOC content:	75.46 %	
-	717.6 g/l / 5.99 lb/gal	
Material VOC content:	717.6 g/l / 5.99 lb/gal	
Solids content:	24.5 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	13,100 mg/kg (rat) >5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

· Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.

(Contd. on page 10)

Page 10/15

(Contd. of page 9)

3

2B

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B988 BASECOAT SILVER DOLLAR FINE

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7 xylene

100-41-4 ethylbenzene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)

US

Page 11/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B988 BASECOAT SILVER DOLLAR FINE

(Contd. of page 10)

Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

UN-Number	UN1263	
DOT, ADR, IMDG, IATA	01/1203	
UN proper shipping name DOT	Paint	
ADR	1263 PAINT	
IMDG, IATA	PAINT	
Transport hazard class(es)	NOT APPLICABLE	
DOT		
n malan er tepe		
Class	3 Flammable liquids	
Label	3	
Class	3 Flammable liquids	
Label	3	
ΙΑΤΑ		
Class	6.1 Toxic substances	
Label	3	
Packing group DOT, ADR, IMDG, IATA	<i>III</i>	

US

Page 12/15

Safety Data Sheet acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B988 BASECOAT SILVER DOLLAR FINE

	(Contd. of page
· Environmental hazards: · Marine pollutant:	No
 Special precautions for user EMS Number: Stowage Category 	Warning: Flammable liquids F-E, <u>S-E</u> A
 Transport in bulk according to Annex MARPOL73/78 and the IBC Code 	<i>I</i> I of Not applicable.
 Transport/Additional information: DOT Quantity limitations 	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

· Section 3	55 (extremely hazardous substances):
None of the	e ingredients is listed.
· Section 31	13 (Specific toxic chemical listings):
1330-20-7	xylene
	ethylbenzene
	butan-1-ol
	1,2,4-trimethylbenzene
7664-38-2	phosphoric acid
	(Contd. on page 13)
	- US

Page 13/15

Safety Data Sheet acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B988 BASECOAT SILVER DOLLAR FINE

TOOA /Tax	in Substances Continue (Anti)	(Contd. of page
•	ric Substances Control Act): n-butyl acetate	ACTIV
1330-20-7	-	ACTIV
	•	ACTIV
	ethylbenzene	-
	butan-1-ol	ACTIV
	1-methoxy-2-propanol	ACTIV
	1,2,4-trimethylbenzene	ACTIV
	mesitylene	ACTIV
	2-methoxy-1-methylethyl acetate	ACTIV
7664-38-2	phosphoric acid	ACTIV
· Hazardous	Air Pollutants	
1330-20-7	-	
100-41-4	ethylbenzene	
· Propositio		
· Chemicals	known to cause cancer:	
100-41-4 e	thylbenzene	
· Chemicals	known to cause reproductive toxicity for females:	
None of the	e ingredients is listed.	
· Chemicals	known to cause reproductive toxicity for males:	
None of the	e ingredients is listed.	
Chemicals	known to cause developmental toxicity:	
None of the	e ingredients is listed.	
Carcinoge	nic categories	
EPA (Envi	ronmental Protection Agency)	
1330-20-7	xylene	
100-41-4	ethylbenzene	
71-36-3	butan-1-ol	
95-63-6	1,2,4-trimethylbenzene	1
108-67-8	mesitylene	1
· TLV (Thre	shold Limit Value)	
1330-20-7		A
100-41-4	ethylbenzene	A
NIOSH-Ca	(National Institute for Occupational Safety and Health)	
	e ingredients is listed.	
	-	(Contd. on page

Page 14/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Trade name: B988 BASECOAT SILVER DOLLAR FINE

Reviewed on 01/10/2025

(Contd. of page 13) · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Warning · Hazard-determining components of labeling: n-butyl acetate ethylbenzene · Hazard statements Flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionarv statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 15) US

Page 15/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2025

Reviewed on 01/10/2025

Trade name: B988 BASECOAT SILVER DOLLAR FINE

(Contd. of page 14)

US

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 01/10/2025 / 1.0

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent. Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Skin Irritation 2: Skin corrosion/irritation - Category 2 Carcinogenicity 2: Carcinogenicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2 • * Data compared to the previous version altered.