



Safety Data Sheet acc. to OSHA HCS

Printing date 01/21/2025

Reviewed on 01/21/2025

1 Identification

- **Product identifier**
- **Trade name:** T550 2K RUBY RED
- **Article number:** T550
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
General Paint Co. SAL
P.O. Box 7623
Beirut
LEBANON
info@hymax.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS07

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

n-butyl acetate

(Contd. on page 2)



Safety Data Sheet acc. to OSHA HCS

Printing date 01/21/2025

Reviewed on 01/21/2025

Trade name: T550 2K RUBY RED

(Contd. of page 1)

methyl methacrylate
2-hydroxyethyl methacrylate

• Hazard statements

Flammable liquid and vapor.
May cause an allergic skin reaction.
May cause drowsiness or dizziness.

• Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

• Classification system:**• NFPA ratings (scale 0 - 4)**

Health = 0
Fire = 3
Reactivity = 0

• HMIS-ratings (scale 0 - 4)

Health = 0
Fire = 3
Reactivity = 0

• Other hazards**• Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

(Contd. on page 3)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 01/21/2025

Reviewed on 01/21/2025

Trade name: T550 2K RUBY RED· **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

123-86-4	n-butyl acetate	>25-≤50%
1330-20-7	xylene	>2.5-≤10%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5-≤10%
80-62-6	methyl methacrylate	≤2.5%
868-77-9	2-hydroxyethyl methacrylate	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)



Safety Data Sheet acc. to OSHA HCS

Printing date 01/21/2025

Reviewed on 01/21/2025

Trade name: T550 2K RUBY RED

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

PAC-1:

123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
80-62-6	methyl methacrylate	17 ppm
868-77-9	2-hydroxyethyl methacrylate	1.9 mg/m ³
97-88-1	n-butyl methacrylate	19 mg/m ³
872-50-4	N-methyl-2-pyrrolidone	30 ppm
100-41-4	ethylbenzene	33 ppm
78-83-1	butanol	150 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m ³
7447-41-8	lithium chloride	2.3 mg/m ³

PAC-2:

123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
80-62-6	methyl methacrylate	120 ppm
868-77-9	2-hydroxyethyl methacrylate	21 mg/m ³
97-88-1	n-butyl methacrylate	210 mg/m ³
872-50-4	N-methyl-2-pyrrolidone	32 ppm
100-41-4	ethylbenzene	1100* ppm

(Contd. on page 5)



Safety Data Sheet

acc. to OSHA HCS

Printing date 01/21/2025

Reviewed on 01/21/2025

Trade name: T550 2K RUBY RED

(Contd. of page 4)

78-83-1	butanol	1,300 ppm
77-58-7	dibutyltin dilaurate	8 mg/m ³
7447-41-8	lithium chloride	17 mg/m ³

· PAC-3:

123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
80-62-6	methyl methacrylate	570 ppm
868-77-9	2-hydroxyethyl methacrylate	1,000 mg/m ³
97-88-1	n-butyl methacrylate	1,300 mg/m ³
872-50-4	N-methyl-2-pyrrolidone	190 ppm
100-41-4	ethylbenzene	1800* ppm
78-83-1	butanol	8000* ppm
77-58-7	dibutyltin dilaurate	48 mg/m ³
7447-41-8	lithium chloride	100 mg/m ³

7 Handling and storage

· Handling:**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities**· Storage:****· Requirements to be met by storerooms and receptacles:** No special requirements.**· Information about storage in one common storage facility:** Not required.**· Further information about storage conditions:** Keep receptacle tightly sealed.**· Storage class:** 3**· Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 6)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 01/21/2025

Reviewed on 01/21/2025

Trade name: T550 2K RUBY RED

(Contd. of page 5)

Control parameters**Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

80-62-6 methyl methacrylate

PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Long-term value: 410 mg/m ³ , 100 ppm
TLV	Short-term value: 100 ppm Long-term value: 50 ppm DSEN, A4

Ingredients with biological limit values:**1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

(Contd. on page 7)

-US-

Safety Data Sheet acc. to OSHA HCS

Printing date 01/21/2025

Reviewed on 01/21/2025

Trade name: T550 2K RUBY RED

(Contd. of page 6)

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:

Fluid

Color:

According to product description

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value:**

Not determined.

- **Change in condition**

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

124 °C (255.2 °F)

(Contd. on page 8)



Safety Data Sheet

acc. to OSHA HCS

Printing date 01/21/2025

Reviewed on 01/21/2025

Trade name: T550 2K RUBY RED

(Contd. of page 7)

· Flash point:	25 °C (77 °F)
· Flammability:	Flammable.
· Auto igniting:	315 °C (599 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
· Density at 20 °C (68 °F):	1.00185 g/cm ³ (8.36044 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	45.0 %
Coating VOC content:	44.96 %
	450.5 g/l / 3.76 lb/gal
Material VOC content:	450.5 g/l / 3.76 lb/gal
· Solids content:	54.7 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.

(Contd. on page 9)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 01/21/2025

Reviewed on 01/21/2025

Trade name: T550 2K RUBY RED

(Contd. of page 8)

- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
80-62-6	methyl methacrylate	3
97-88-1	n-butyl methacrylate	2B
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 10)



Safety Data Sheet

acc. to OSHA HCS

Printing date 01/21/2025

Reviewed on 01/21/2025

Trade name: T550 2K RUBY RED


(Contd. of page 9)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint
- **ADR** 1263 PAINT
- **IMDG, IATA** PAINT
- **Transport hazard class(es)** NOT APPLICABLE
- **DOT**
- 
- **Class** 3 Flammable liquids

(Contd. on page 11)

US



Safety Data Sheet


acc. to OSHA HCS

Printing date 01/21/2025

Reviewed on 01/21/2025

Trade name: T550 2K RUBY RED

(Contd. of page 10)

· Label	3
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· EMS Number:	F-E, S-E
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

(Contd. on page 12)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 01/21/2025

Reviewed on 01/21/2025

Trade name: T550 2K RUBY RED

(Contd. of page 11)

• Sara**• Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

• Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

80-62-6 methyl methacrylate

872-50-4 N-methyl-2-pyrrolidone

100-41-4 ethylbenzene

• TSCA (Toxic Substances Control Act):

123-86-4 n-butyl acetate

ACTIVE

1330-20-7 xylene

ACTIVE

108-65-6 2-methoxy-1-methylethyl acetate

ACTIVE

80-62-6 methyl methacrylate

ACTIVE

868-77-9 2-hydroxyethyl methacrylate

ACTIVE

97-88-1 n-butyl methacrylate

ACTIVE

136-53-8 ZINC 2-ETHYLEXANOATE

ACTIVE

872-50-4 N-methyl-2-pyrrolidone

ACTIVE

100-41-4 ethylbenzene

ACTIVE

78-83-1 butanol

ACTIVE

64742-88-7 Solvent naphtha (petroleum), medium aliph.

ACTIVE

77-58-7 dibutyltin dilaurate

ACTIVE

7447-41-8 lithium chloride

ACTIVE

• Hazardous Air Pollutants

1330-20-7 xylene

80-62-6 methyl methacrylate

100-41-4 ethylbenzene

• Proposition 65**• Chemicals known to cause cancer:**

100-41-4 ethylbenzene

• Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

• Chemicals known to cause developmental toxicity:

872-50-4 N-methyl-2-pyrrolidone

(Contd. on page 13)



Safety Data Sheet acc. to OSHA HCS

Printing date 01/21/2025

Reviewed on 01/21/2025

Trade name: T550 2K RUBY RED

(Contd. of page 12)

· Carcinogenic categories**· EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
80-62-6	methyl methacrylate	E, NL
100-41-4	ethylbenzene	D

· TLV (Threshold Limit Value)

1330-20-7	xylene	A4
80-62-6	methyl methacrylate	A4
100-41-4	ethylbenzene	A3
77-58-7	dibutyltin dilaurate	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms

GHS02 GHS07

· Signal word Warning**· Hazard-determining components of labeling:**

n-butyl acetate
methyl methacrylate
2-hydroxyethyl methacrylate

· Hazard statements

Flammable liquid and vapor.
May cause an allergic skin reaction.
May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 14)



Safety Data Sheet acc. to OSHA HCS

Printing date 01/21/2025

Reviewed on 01/21/2025

Trade name: T550 2K RUBY RED

(Contd. of page 13)

*IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.*

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** Product safety department

• **Contact:** N/A

• **Date of preparation / last revision** 01/21/2025 / 1.0

• **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Sensitization - Skin 1: Skin sensitisation – Category 1

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

• *** Data compared to the previous version altered.**